



# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-02-18 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g  
Product code : 1006139  
Part number : 73005

#### 1.2. Recommended use and restrictions on use

Recommended use : Multi-Purpose Lubricant  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Aerosol, Category 1 : Extremely flammable aerosol. Pressurized container; may burst if heated.  
Aspiration hazard, Category 1 : May be fatal if swallowed and enters airways.  
Hazardous to the aquatic environment, Acute Hazard, Category 2 : Toxic to aquatic life.

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) :

Danger

Hazard statements (GHS CA) :

Extremely flammable aerosol  
Pressurized container; may burst if heated  
May be fatal if swallowed and enters airways

Precautionary statements (GHS CA) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
Do NOT induce vomiting.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container in accordance with local/regional/national regulations.

### 2.3. Other hazards

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	45 – 70
White mineral oil (petroleum)	White mineral oil (petroleum)	CAS-No.: 8042-47-5	10 – 30
Carbon dioxide	Carbon dioxide	CAS-No.: 124-38-9	1 – 5
Petrolatum	Petrolatum	CAS-No.: 8009-03-8	0.5 – 1.5
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	0.1 – 1

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Alcohol resistant foam. Carbon dioxide.

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.
Precautionary measures fire	: Keep container tightly closed and away from heat, sparks and flame.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures	: Self-contained breathing apparatus.

### 6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product usage instructions, see the product label.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Level 3 Aerosol. Store locked up. Store in a well-ventilated place. Store in a cool, dry place out of direct sunlight. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Packaging materials	: Store always product in container of same material as original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Carbon dioxide (124-38-9)	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54000 mg/m <sup>3</sup>
	30000 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
VECD (OEL STEV)	54000 mg/m <sup>3</sup>
	30000 ppm
VEMP (OEL TWA EV)	9000 mg/m <sup>3</sup>
	5000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Carbon dioxide (124-38-9)</b>	
OEL STEL	15000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWAEV	5000 ppm
	30000 ppm

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Carbon dioxide (124-38-9)</b>	
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Nitrile. Neoprene.

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Amber  
Odor : Mild petroleum.  
Melting point : -49 °C (-56.2 °F) estimated  
Freezing point : -49 °C (-56.2 °F) estimated  
Boiling point : 100 °C (212 °F) estimated  
Flammability (solid, gas) : Not applicable

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Explosion limits	: Lower explosion limit: 0.5 % estimated Upper explosion limit: 0.5 % estimated
Flash point	: 93.3 °C (200 °F) Setflash
Auto-ignition temperature	: 220 °C (220 °C) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: Negligible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: 2580.4 hPa estimated
Density	: No data available
Relative density	: 0.82 (Concentrate)
Relative vapor density at 20°C	: > 1 (air=1)
Particle characteristics	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid temperatures exceeding the flash point. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Combustible materials. Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO <sub>2</sub> ). Sulfur oxides (SO <sub>x</sub> ). Hydrogen sulfide. Mercaptans. Sulfides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
<b>Petrolatum (8009-03-8)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	3600 mg/kg Source: International Uniform Chemical Information Database
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg Source: International Uniform Chemical Information Database

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
<b>Distillates (petroleum), hydrotreated light</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified.
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
<b>Petrolatum (8009-03-8)</b>	
LOAEL (dermal,rat/rabbit,90 days)	200 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (dermal,rat/rabbit,90 days)	≥ 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>White mineral oil (petroleum) (8042-47-5)</b>	
NOAEL (oral,rat,90 days)	≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life.

<b>Carbon dioxide (124-38-9)</b>	
LC50 - Fish [1]	35 mg/l Source: HSDB
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LC50 - Fish [1]	2.4 mg/l Source: ECOTOX
<b>Petrolatum (8009-03-8)</b>	
LC50 - Fish [1]	0.00000009 mg/l Source: Quantitative Structure Activity Relation
EC50 96h - Algae [1]	0.00000022 mg/l Source: Quantitative Structure Activity Relation
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
<b>White mineral oil (petroleum) (8042-47-5)</b>	
LC50 - Fish [1]	> 10000 mg/l Source: IUCLID

#### 12.2. Persistence and degradability

<b>CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g</b>	
Persistence and degradability	No data is available on the degradability of this product.

#### 12.3. Bioaccumulative potential

<b>Carbon dioxide (124-38-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.83 Source: ISCS
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
<b>Petrolatum (8009-03-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	6 Source: International Chemical Safety Cards
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
<b>White mineral oil (petroleum) (8042-47-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	5.18 Source: Quantitative Structure Activity Relation

#### 12.4. Mobility in soil

No additional information available

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 12.5. Other adverse effects

Ozone : Not classified




## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.  
Additional information : Contents under pressure.

## SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
<b>14.1. UN number</b>		
UN1950	1950	1950
<b>14.2. Proper Shipping Name</b>		
Aerosols, flammable (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
<b>14.3. Transport hazard class(es)</b>		
LTD QTY	LTD QTY	LTD QTY
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
No supplementary information available		

### 14.6. Special precautions for user

#### TDG

TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gases  
UN-No. (TDG) : UN1950  
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.  
(2) Subsection (1) does not apply to self-defence spray.

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

### IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### Carbon dioxide (124-38-9)

Listed on the Canadian DSL (Domestic Substances List)

#### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Petrolatum (8009-03-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

# CRC® 3-36® Multi-Purpose Precision Lubricant, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### White mineral oil (petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

## 15.2. International regulations

### Carbon dioxide (124-38-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Petrolatum (8009-03-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### White mineral oil (petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content

0 %

Product Category

Lubricants, multi-purpose lubricants that are not solid or semi-solid.

## SECTION 16: Other information

Issue date : 02-18-2025

Other information : CRC # 591C/1002617.  
Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.