



# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-05-27 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® Extreme Duty Silicone, 283 g  
Product code : 1006145  
Part number : 73030

#### 1.2. Recommended use and restrictions on use

Recommended use : Silicone-based multi-purpose lubricant  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 2B	Causes eye irritation.
Reproductive toxicity, Category 2	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment, Acute Hazard, Category 2	Toxic to aquatic life.
Hazardous to the aquatic environment, Chronic Hazard, Category 2	Toxic to aquatic life with long lasting effects.

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : Extremely flammable aerosol  
Pressurized container; may burst if heated  
May be fatal if swallowed and enters airways

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA)	: Causes skin and eye irritation May cause drowsiness or dizziness Suspected of damaging fertility or the unborn child : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, eye and face protection. IF SWALLOWED: Immediately call a POISON CENTER or a doctor. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice or attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national regulations.
-----------------------------------	--

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	45 – 80
Ethane, 1,1-difluoro-	1,1-Difluoroethane (HFC-152a)	CAS-No.: 75-37-6	30 – 60
Siloxanes and Silicones, di-Me	Siloxanes and Silicones, di-Me	CAS-No.: 63148-62-9	1 – 5
Hexane	n-Hexane ; Hexane	CAS-No.: 110-54-3	1 – 5

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim ingested the substance. Call a physician immediately.
First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician immediately.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: Risk of lung edema. Aspiration may cause pulmonary edema and pneumonitis.

#### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media	: Water fog. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

#### 5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	--

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Personal Precautions, Protective Equipment and Emergency Procedures : Self-contained breathing apparatus.

### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.

Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.

Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.

Hygiene measures : Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Level 3 Aerosol. Store locked up. Keep in fireproof place. Store in a well-ventilated place. Store in a cool, dry place out of direct sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Hexane (110-54-3)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	n-Hexane
VEMP (OEL TWAEV)	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	20 ppm

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Hexane (110-54-3)</b>	
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Hexane (110-54-3)</b>	
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWAEV	50 ppm
Notations and remarks	Skin
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	n-Hexane
OEL TWA	176 mg/m <sup>3</sup> 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Nitrile. Fluoroelastomer (FKM)

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Mild solvent
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 50.6 °C (123 °F) estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: Lower explosion limit: 1.3 % estimated Upper explosion limit: 7.3 % estimated
Flash point	: -17 °C (1.4 °F) estimated
Auto-ignition temperature	: 254 °C (489.2 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: No data available
Density	: No data available
Relative density	: 0.76 estimated
Relative vapor density at 20°C	: > 1 (air=1)
Particle characteristics	: No data available

#### 9.2. Additional Regulatory Information

No additional information available

### SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO <sub>2</sub> ). Halogenated compounds. Formaldehyde.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Siloxanes and Silicones, di-Me (63148-62-9)

LD50 oral rat	> 17000 mg/kg Source: National Library of Medicine
LD50 dermal rabbit	> 2000 mg/kg Source: National Library of Medicine

#### Naphtha (petroleum), hydrotreated light (64742-49-0)

LD50 oral rat	> 5000 mg/kg Source: IUCLID
---------------	-----------------------------

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 23300 mg/l

<b>Hexane (110-54-3)</b>	
LD50 oral rat	24 ml/kg Source: ECHA
LD50 dermal rabbit	> 3350 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
LC50 Inhalation - Rat (Vapors)	259.354 mg/l Source: ECHA

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male

<b>Hexane (110-54-3)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
Viscosity, kinematic	0.67 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: Risk of lung edema. Aspiration may cause pulmonary edema and pneumonitis.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

<b>Ethane, 1,1-difluoro- (75-37-6)</b>	
LC50 - Fish [1]	450 mg/l Source: OECD Screening Information Data Set
LC50 - Fish [2]	719.611 mg/l Test organisms (species):
EC50 - Crustacea [1]	980 mg/l Source: OECD Screening Information Data Set

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Ethane, 1,1-difluoro- (75-37-6)</b>	
EC50 - Other aquatic organisms [1]	146.695 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	419 mg/l Source: OECD Screening Information Data Set
<b>Siloxanes and Silicones, di-Me (63148-62-9)</b>	
LC50 - Fish [1]	37.79 mg/l Source: The ECOTOXicology database
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LC50 - Fish [1]	> 3 mg/l
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	4.6 mg/l waterflea
EC50 - Other aquatic organisms [2]	10 mg/l
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>Hexane (110-54-3)</b>	
LC50 - Fish [1]	> 1 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	50 mg/l waterflea

### 12.2. Persistence and degradability

#### CRC® Extreme Duty Silicone, 283 g

Persistence and degradability No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

<b>Ethane, 1,1-difluoro- (75-37-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.13 Source: SIDS
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
<b>Hexane (110-54-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 Source: ICSC

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet




according to the Hazardous Products Regulation (WHMIS 2015)

Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

Additional information : Do not re-use empty containers.

### SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
<b>14.1. UN number</b>		
UN1950	1950	1950
<b>14.2. Proper Shipping Name</b>		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
<b>14.3. Transport hazard class(es)</b>		
LTD QTY	LTD QTY	LTD QTY
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Marine Pollutant Exception		

### 14.6. Special precautions for user

**TDG**

TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gases

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.

(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

Emergency Response Guide (ERG) Number : 126

**IMDG**

Class (IMDG) : 2.1 - Flammable gases

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### CRC® Extreme Duty Silicone, 283 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Ethane, 1,1-difluoro-	75-37-6	Listed on the Canadian DSL (Domestic Substances List)
Siloxanes and Silicones, di-Me	63148-62-9	Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed on the Canadian DSL (Domestic Substances List)
Hexane	110-54-3	Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

#### Ethane, 1,1-difluoro- (75-37-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

# CRC® Extreme Duty Silicone, 283 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Siloxanes and Silicones, di-Me (63148-62-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	59.96 %
Product Category	Lubricants, silicone-based multi-purpose lubricants that are not solid or semi-solid

## SECTION 16: Other information

Issue date : 05-27-2025  
Other information : CRC # 1752517.  
Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.