



# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-08-01 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® Multi-Purpose Bearing Grease, 396 g  
Product code : 1006200  
Part number : 73312

#### 1.2. Recommended use and restrictions on use

Recommended use : Bearing grease  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Precautionary statements (GHS CA) : Observe good industrial hygiene practices.  
Wash hands thoroughly after handling.  
Store away from incompatible materials  
Dispose of contents/container in accordance with local/regional/national regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 3.2. Mixtures

| Name   | Chemical name / Synonyms                               | Product identifier  | %       |
|--|--|---------------------|---------|
| Paraffin oils (petroleum), catalytic dewaxed heavy     | Paraffin oils (petroleum), catalytic dewaxed heavy     | CAS-No.: 64742-70-7 | 45 – 75 |
| Distillates (petroleum), hydrotreated heavy paraffinic | Distillates (petroleum), hydrotreated heavy paraffinic | CAS-No.: 64742-54-7 | 5 – 10  |
| Carbonic acid calcium salt (1:1)                       | Calcium carbonate                                      | CAS-No.: 471-34-1   | 1 – 5   |

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.3. Specific hazards arising from the hazardous product

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use. Wear personal protective equipment. For product usage instructions, see the product label.

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Store in a cool, dry place out of direct sunlight.

Packaging materials : Store always product in container of same material as original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Carbonic acid calcium salt (1:1) (471-34-1)            |   |
|--|---|
| <b>Canada (Quebec) - Occupational Exposure Limits</b>  |   |
| Local name   | Calcium carbonate   |
| VEMP (OEL TWAEV)                                       | 10 mg/m <sup>3</sup> Td   |
| Regulatory reference                                   | S-2.1, r. 13 - Regulation respecting occupational health and safety |
| <b>Canada (Nunavut) - Occupational Exposure Limits</b> |   |
| Local name   | Limestone (calcium carbonate)                                       |
| OEL TWA  | 10 mg/m <sup>3</sup>  |
| OEL STEL   | 20 mg/m <sup>3</sup>  |

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                   |  |
|--|--|
| Regulatory reference   | Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021) |
| <b>Canada (Northwest Territories) - Occupational Exposure Limits</b> |  |
| Local name   | Limestone (calcium carbonate)  |
| OEL TWA  | 10 mg/m <sup>3</sup>   |
| OEL STEL   | 20 mg/m <sup>3</sup>   |
| Regulatory reference   | Occupation Health and Safety Regulations R-039-2015 (R-090-2024)                   |
| <b>Canada (Saskatchewan) - Occupational Exposure Limits</b>          |  |
| Local name   | Limestone (calcium carbonate)  |
| OEL TWA  | 10 mg/m <sup>3</sup>   |
| OEL STEL   | 20 mg/m <sup>3</sup>   |
| Regulatory reference   | The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10        |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Neoprene. Nitrile

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Blue  
Odor : Mild petroleum.

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|   |  |
|---|--|
| Melting point                                   | : Not applicable                       |
| Freezing point                                  | : No data available                    |
| Boiling point                                   | : 360 °C (680 °F) (estimated)          |
| Flammability (solid, gas)                       | : Not applicable                       |
| Explosion limits                                | : No data available                    |
| Flash point                                     | : 243 °C (469.4 °F) Cleveland Open-cup |
| Auto-ignition temperature                       | : 260 °C (500 °F) (estimated)          |
| Decomposition temperature                       | : No data available                    |
| pH  | : No data available                    |
| Viscosity, kinematic                            | : No data available                    |
| Solubility                                      | : Water: Insoluble                     |
| Partition coefficient n-octanol/water (Log Pow) | : No data available                    |
| Vapor pressure                                  | : No data available                    |
| Evaporation rate                                | : No data available                    |
| Density   | : No data available                    |
| Relative density                                | : 0.95                                 |
| Relative vapor density at 20°C                  | : No data available                    |
| Particle characteristics                        | : No data available                    |

### 9.2. Additional Regulatory Information

No additional information available

## SECTION 10: Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.                   |
| Chemical stability                 | : Stable under normal conditions.  |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use.   |
| Conditions to avoid                | : None under recommended storage and handling conditions (see section 7).                              |
| Incompatible materials             | : None known.  |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b> |  |
|--|--|
| LD50 oral rat  | > 15000 mg/kg Source: IUCLID   |
| LD50 dermal rabbit   | > 5000 mg/kg Source: IUCLID  |
| <b>Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)</b>     |  |
| LD50 oral rat  | > 5000 mg/kg Source: ECHA  |
| LD50 dermal rabbit   | > 2000 mg/kg Source: ECHA  |
| LC50 Inhalation - Rat (Dust/Mist)  | > 2.18 mg/l Source: ECHA   |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
| LD50 oral rat  | 6450 mg/kg Source: International Uniform Chemical Information Database |
| LD50 dermal rat  | > 2000 mg/kg Source: ECHA  |

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
|--|--|
| LC50 Inhalation - Rat  | > 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) |
| LC50 Inhalation - Rat (Dust/Mist)  | > 3 mg/l Source: ECHA  |
| LC50 Inhalation - Rat (Vapors)   | > 3 mg/l/4h  |
| Skin corrosion/irritation  | : Not classified   |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
| pH   | 8 – 9 Source: HSDB   |
| Serious eye damage/irritation  | : Not classified   |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
| pH   | 8 – 9 Source: HSDB   |
| Respiratory or skin sensitization  | : Not classified   |
| Germ cell mutagenicity   | : Not classified   |
| Carcinogenicity  | : Not classified   |
| Reproductive toxicity  | : Not classified   |
| STOT-single exposure   | : Not classified   |
| STOT-repeated exposure   | : Not classified   |
| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b> |  |
| LOAEL (oral,rat,90 days)   | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)   |
| NOAEC (inhalation,rat,dust/mist/fume,90 days)                              | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)  |
| <b>Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)</b>     |  |
| LOAEL (oral,rat,90 days)   | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)   |
| NOAEC (inhalation,rat,dust/mist/fume,90 days)                              | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)  |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
| NOAEL (oral,rat,90 days)   | 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)                                |
| NOAEC (inhalation, rat, 90 days)   | 0.399 mg/l   |
| NOAEC (inhalation,rat,dust/mist/fume,90 days)                              | ≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)   |
| Aspiration hazard  | : Not classified   |
| Symptoms/effects after inhalation  | : None under normal conditions.  |
| Symptoms/effects after skin contact  | : Prolonged or repeated contact may cause skin to become dry.  |
| Symptoms/effects after eye contact   | : Direct contact with the eyes is likely to be irritating.   |
| Symptoms/effects after ingestion   | : None under normal conditions.  |

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b> |  |
|--|--|
| LC50 - Fish [1]  | > 5000 mg/l  |
| EC50 - Crustacea [1]   | > 1000 mg/l Source: IUCLID   |
| EC50 96h - Algae [1]   | > 1000 mg/l Source: IUCLID   |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |  |
| LC50 - Fish [1]  | > 56000 mg/l Source: ECOTOX  |
| EC50 - Other aquatic organisms [1]   | > 100 mg/l waterflea   |
| ErC50 algae  | > 14 mg/l  |
| EC50 72h - Algae [1]   | > 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 96h - Algae [1]   | 22000 mg/l Source: Ecological Structure Activity Relationships                                       |

#### 12.2. Persistence and degradability

| <b>CRC® Multi-Purpose Bearing Grease, 396 g</b> |  |
|---|--|
| Persistence and degradability                   | No data is available on the degradability of this product. |

#### 12.3. Bioaccumulative potential

| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b> |                        |
|--|------------------------|
| Partition coefficient n-octanol/water (Log Pow)                            | 3.9 – 6 Source: IUCLID |
| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b>                         |                        |
| Partition coefficient n-octanol/water (Log Pow)                            | -2.12                  |

#### 12.4. Mobility in soil

| <b>Carbonic acid calcium salt (1:1) (471-34-1)</b> |  |
|--|--|
| Mobility in soil                                   | 4.971 Source: Quantitative Structure Activity Relation |

#### 12.5. Other adverse effects

Ozone : Not classified

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

| TDG                                     | IMDG           | IATA           |
|---|----------------|----------------|
| <b>14.1. UN number</b>                  |                |                |
| Not regulated.                          | Not regulated. | Not regulated. |
| <b>14.2. Proper Shipping Name</b>       |                |                |
| Not regulated.                          | Not regulated. | Not regulated. |
| <b>14.3. Transport hazard class(es)</b> |                |                |
| Not regulated.                          | Not regulated. | Not regulated. |
| <b>14.4. Packing group</b>              |                |                |
| Not regulated.                          | Not regulated. | Not regulated. |
| <b>14.5. Environmental hazards</b>      |                |                |
| No supplementary information available  |                |                |

### 14.6. Special precautions for user

#### TDG

Not regulated.

#### IMDG

Not regulated.

#### IATA

Not regulated.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. National regulations

#### CRC® Multi-Purpose Bearing Grease, 396 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

| Name   | CAS-No.    | Regulatory reference                                  |
|--|------------|---|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | Listed on the Canadian DSL (Domestic Substances List) |
| Paraffin oils (petroleum), catalytic dewaxed heavy     | 64742-70-7 | Listed on the Canadian DSL (Domestic Substances List) |
| Carbonic acid calcium salt (1:1)                       | 471-34-1   | Listed on the Canadian DSL (Domestic Substances List) |

# CRC® Multi-Purpose Bearing Grease, 396 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 15.2. International regulations

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

#### Carbonic acid calcium salt (1:1) (471-34-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

|                  |                |
|------------------|----------------|
| VOC content      | 0 %            |
| Product Category | Not regulated. |

## SECTION 16: Other information

Issue date : 08-01-2025

Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.