



CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-05-08 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Gasket Kleen™, 340 g
Product code : 1006292
Part number : 75021

1.2. Recommended use and restrictions on use

Recommended use : Gasket remover
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Carcinogenicity, Category 2

Reproductive toxicity, Category 1B

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Specific target organ toxicity, Repeated exposure, Category 2

Hazardous to the aquatic environment, Acute Hazard, Category 3

Extremely flammable aerosol. Pressurized container; may burst if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause respiratory irritation.

May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure.

Harmful to aquatic life.

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) :

Danger

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hazard statements (GHS CA)	: Extremely flammable aerosol Pressurized container; may burst if heated Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Suspected of causing cancer. May damage fertility or the unborn child May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure.
Precautionary statements (GHS CA)	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection. Wash hands thoroughly after handling. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice or attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Acetone	acetone, propan-2-one, propanone	CAS-No.: 67-64-1	45 – 75
N-methyl-2-pyrrolidone	1-Methyl-2-pyrrolidinone	CAS-No.: 872-50-4	10 – 30
Petroleum gases, liquefied, sweetened	Petroleum gases, liquefied, sweetened	CAS-No.: 68476-86-8	10 – 30
xylene	Xylene	CAS-No.: 1330-20-7	1 – 5

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%
ethylbenzene	ethylbenzene	CAS-No.: 100-41-4	0.1 – 1

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness. May cause respiratory irritation.

Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.

Chronic symptoms : May damage fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
- Personal Precautions, Protective Equipment and Emergency Procedures : Self-contained breathing apparatus.

6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.
- Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not use if spray button is missing or defective. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with skin and eyes. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 3 Aerosol. Store locked up. Keep in fireproof place. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Xylene (o-,m-,p-isomers) (Dimethylbenzene)

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

xylene (1330-20-7)	
OEL TWA	434 mg/m ³
	100 ppm
OEL STEL	651 mg/m ³
	150 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Xylene (o-, m-, p- isomers) (Dimethylbenzene)
VECD (OEL STEV)	651 mg/m ³
	150 ppm
VEMP (OEL TWA EV)	434 mg/m ³
	100 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Xylene
OEL TWA	100 ppm
OEL STEL	150 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS impair; Hematologic eff; Ototoxicity (p-xylene). Notations: OTO (Ototoxicant) (p isomer); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Xylene
OEL TWA	100 ppm
OEL STEL	150 ppm
Notations and remarks	URT & eye irr; CNS impair
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS impair; Hematologic eff; Ototoxicity (p-xylene). Notations: OTO (Ototoxicant) (p isomer); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

xylene (1330-20-7)	
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS impair; Hematologic eff; Ototoxicity (p-xylene). Notations: OTO (Ototoxicant) (p isomer); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Xylene (o, m-, p-isomers)
OEL TWA	100 ppm
OEL STEL	150 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Xylene (o, m-, p-isomers)
OEL TWA	100 ppm
OEL STEL	150 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Xylene (o, m & p isomers)
OEL TWAEV	100 ppm 150 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr; CNS impair; Hematologic eff; Ototoxicity (p-xylene). Notations: OTO (Ototoxicant) (p isomer); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Xylene (o-, m-, p-isomers)
OEL TWA	100 ppm
OEL STEL	150 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethylbenzene (100-41-4)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	434 mg/m ³
	100 ppm
OEL STEL	543 mg/m ³
	125 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Ethyl benzene
VEMP (OEL TWAEV)	20 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Ethylbenzene
OEL TWA	20 ppm
Notations and remarks	IARC group 2B carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	20 ppm

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethylbenzene (100-41-4)	
Notations and remarks	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	100 ppm
OEL STEL	125 ppm
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWAEV	20 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Ethyl benzene
OEL TWA	100 ppm
OEL STEL	125 ppm
Notations and remarks	Designated Chemical Substance
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acetone (67-64-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	1200 mg/m ³
	500 ppm
OEL STEL	1800 mg/m ³
	750 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Acetone
VECD (OEL STEV)	500 ppm
VEMP (OEL TWA EV)	250 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	594 mg/m ³
	250 ppm
OEL STEL	1187 mg/m ³
	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	eye irr; CNS impair; BEI
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	594 mg/m ³
	250 ppm

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acetone (67-64-1)	
OEL STEL	1187 mg/m ³ 500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	594 mg/m ³ 250 ppm
OEL STEL	1187 mg/m ³ 500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Acetone
OEL TWAEV	250 ppm 500 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	594 mg/m ³ 250 ppm
OEL STEL	1187 mg/m ³ 500 ppm

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acetone (67-64-1)	
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
N-methyl-2-pyrrolidone (872-50-4)	
Canada (Ontario) - Occupational Exposure Limits	
Local name	N-Methyl-2-pyrrolidone
OEL TWAEV	400 mg/m ³
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Petroleum gases, liquefied, sweetened (68476-86-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Butane
VEMP (OEL TWAEV)	1900 mg/m ³ 800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm
Notations and remarks	Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
OEL TWAEV	1000 ppm
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Butyl rubber

Eye protection:

Wear safety glasses with side shields (or goggles).

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Colorless
Odor : Solvent
Melting point : -95.4 °C (-139.6 °F) estimated
Freezing point : -95.4 °C (-139.6 °F) estimated
Boiling point : 56 °C (132.8 °F) estimated
Flammability (solid, gas) : Not applicable
Explosion limits : No data available
Flash point : -20 °C (-4 °F) estimated
Auto-ignition temperature : 232.33 °C (450 °F) estimated
Decomposition temperature : No data available
pH : No data available
Viscosity, kinematic : No data available
Solubility : Water: Soluble
Partition coefficient n-octanol/water (Log Pow) : No data available
Vapor pressure : No data available
Evaporation rate : Fast
Density : 7.09 lb/gal Concentrate
Relative density : 0.85 Concentrate
Relative vapor density at 20°C : No data available
Particle characteristics : No data available

9.2. Additional Regulatory Information

No additional information available

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Acids. Strong oxidizing agents. Strong acids. Halogens. Peroxides. Phenols.
Hazardous decomposition products	: Carbon oxides (CO, CO ₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	> 4200 mg/kg
LC50 Inhalation - Rat [ppm]	5922 ppm
LC50 Inhalation - Rat (Dust/Mist)	> 10000 mg/l
LC50 Inhalation - Rat (Vapors)	29 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg Source: ECHA, HSDB
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm Source: ECHA, Harmonized classification of EU CLP
LC50 Inhalation - Rat (Dust/Mist)	17200 mg/l
LC50 Inhalation - Rat (Vapors)	18.96 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg Source: ECHA
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA
N-methyl-2-pyrrolidone (872-50-4)	
LD50 oral rat	4150 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5.1 mg/l Source: ECHA
LC50 Inhalation - Rat (Vapors)	> 5.1 mg/l/4h
Petroleum gases, liquefied, sweetened (68476-86-8)	
LC50 Inhalation - Rat (Dust/Mist)	658 mg/l Source: IUCLID

Skin corrosion/irritation : Causes skin irritation.

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Serious eye damage/irritation : Causes serious eye irritation.

N-methyl-2-pyrrolidone	
pH	7.7 – 8 Source: HSDB
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

xylene (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

N-methyl-2-pyrrolidone (872-50-4)	
NOAEL (chronic,oral,animal/male,2 years)	≈ 89 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)
NOAEL (chronic,oral,animal/female,2 years)	≈ 221 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)

Reproductive toxicity : May damage fertility or the unborn child.

Acetone	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male

N-methyl-2-pyrrolidone	
LOAEL (animal/female, F0/P)	500 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/male, F0/P)	≥ 500 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/female, F0/P)	350 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure.

xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bw/day
NOAEC (inhalation, rat, gas, 90 days)	> 810 ppm

ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Acetone (67-64-1)	
NOAEL (oral, rat, 90 days)	900 mg/kg bw/day

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

N-methyl-2-pyrrolidone (872-50-4)	
LOAEL (dermal, rat/rabbit, 90 days)	1653 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 28 days)	820 mg/kg bw/day
NOAEL (dermal, rat/rabbit, 28 days)	< 413 mg/kg bw/day
NOAEC (inhalation, rat, 28 days)	0.1 mg/l
NOAEL (oral, rat, 90 days)	169 mg/kg bw/day
NOAEL (dermal, rat/rabbit, 90 days)	826 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, 90 days)	0.5 mg/l

Petroleum gases, liquefied, sweetened (68476-86-8)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard : Not classified

xylene (1330-20-7)	
Viscosity, kinematic	0.86 mm ² /s

ethylbenzene (100-41-4)	
Viscosity, kinematic	0.641 mm ² /s

N-methyl-2-pyrrolidone (872-50-4)	
Viscosity, kinematic	1615.759 mm ² /s

Symptoms/effects : May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.
Chronic symptoms : May damage fertility or the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Source: ECHA
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Other aquatic organisms [1]	350 mg/l waterflea
EC50 - Other aquatic organisms [2]	3.9 mg/l
NOEC chronic fish	> 1.3 mg/l
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	2.2 mg/l waterflea
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	2.6 mg/l Source: ECHA
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

Acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l Source: ECHA
EC50 - Crustacea [1]	12600 – 12700 mg/l
EC50 - Other aquatic organisms [1]	12600 mg/l waterflea
EC50 - Other aquatic organisms [2]	3400 mg/l
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

N-methyl-2-pyrrolidone (872-50-4)	
LC50 - Fish [1]	> 500 mg/l
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
EC50 72h - Algae [1]	> 500 mg/l
EC50 72h - Algae [2]	672.8 mg/l Test organisms (species): Desmodemus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	12.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

CRC® Gasket Kleen™, 340 g	
Persistence and degradability	No data is available on the degradability of this product.

12.3. Bioaccumulative potential

xylene (1330-20-7)	
BCF - Fish [1]	< 25.9 l/kg
Partition coefficient n-octanol/water (Log Pow)	3.16

ethylbenzene (100-41-4)	
BCF - Fish [1]	1 l/kg
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB

Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Kow)	-0.23
N-methyl-2-pyrrolidone (872-50-4)	
BCF - Fish [1]	3.16 l/kg
Partition coefficient n-octanol/water (Log Pow)	-0.46
Petroleum gases, liquefied, sweetened (68476-86-8)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified




SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No		

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

CRC® Gasket Kleen™, 340 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
xylene	1330-20-7	Listed on the Canadian DSL (Domestic Substances List)
ethylbenzene	100-41-4	Listed on the Canadian DSL (Domestic Substances List)
Acetone	67-64-1	Listed on the Canadian DSL (Domestic Substances List)
N-methyl-2-pyrrolidone	872-50-4	Listed on the Canadian DSL (Domestic Substances List)
Petroleum gases, liquefied, sweetened	68476-86-8	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

N-methyl-2-pyrrolidone (872-50-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Petroleum gases, liquefied, sweetened (68476-86-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content

47.5 %

Product Category

Adhesive remover, gasket or thread-locking adhesive remover, including products designed for use as both a paint stripper and gasket or thread-locking adhesive remover.

CRC® Gasket Kleen™, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 16: Other information

Issue date : 05-08-2025

Other information : CRC # 1002570.

Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.