



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Heavy Duty Silicone Lubricant - 212g</b>
<b>Other means of identification</b>	
<b>Product Code</b>	No. 75074 (Item# 1006320)
<b>Recommended use</b>	Silicone-based multi-purpose lubricant
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufactured or sold by:</b>	
<b>Company name</b>	CRC Canada Co.
<b>Address</b>	83 Galaxy Blvd Unit 35 - 37 Toronto, ON M9W 5X6 Canada
<b>Telephone</b>	
<b>General Information</b>	416-847-7750
<b>Technical Assistance</b>	800-556-5074
<b>24-Hour Emergency (CHEMTREC)</b>	800-424-9300 (Canada)
<b>Website</b>	crcindustries.ca

## 2. Hazard identification

<b>Physical hazards</b>	Aerosols	Category 1
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.
<b>Precautionary statement</b>	
<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapors. Wear protective gloves and eye/face protection. Wash thoroughly after handling.
<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Supplemental information</b>	None.
<b>Other hazards</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	30 - 60
liquefied petroleum gas		68476-86-8	15 - 40
naphtha (petroleum), hydrotreated light		64742-49-0	10 - 30
heptane, branched, cyclic and linear		426260-76-6	3 - 7
n-heptane		142-82-5	3 - 7
solvent naphtha (petroleum), light aliph.		64742-89-8	0.5 - 1.5

The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

---

## 7. Handling and storage

### Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist/vapors. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

---

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
acetone (CAS 67-64-1)	STEL	1800 mg/m3
		750 ppm
	TWA	1200 mg/m3
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	500 ppm
		1590 mg/m3
		400 ppm

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
n-heptane (CAS 142-82-5)	STEL	2050 mg/m <sup>3</sup> 500 ppm
	TWA	1640 mg/m <sup>3</sup> 400 ppm
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1590 mg/m <sup>3</sup> 400 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

**Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)**

Components	Type	Value
acetone (CAS 67-64-1)	STEL	1728 mg/m <sup>3</sup> 750 ppm
		TWA
	TWA	1590 mg/m <sup>3</sup> 400 ppm
n-heptane (CAS 142-82-5)	STEL	2050 mg/m <sup>3</sup> 500 ppm
	TWA	1640 mg/m <sup>3</sup> 400 ppm
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1590 mg/m <sup>3</sup> 400 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	525 mg/m <sup>3</sup>
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	525 mg/m <sup>3</sup>

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value
acetone (CAS 67-64-1)	STEL	2380 mg/m <sup>3</sup>
		1000 ppm
	TWA	1190 mg/m <sup>3</sup>
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		500 ppm
	TWA	1000 mg/m <sup>3</sup>
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1000 mg/m <sup>3</sup>

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

Components	Type	Value
acetone (CAS 67-64-1)	15 minute	750 ppm
	8 hour	500 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	15 minute	500 ppm
	8 hour	400 ppm
n-heptane (CAS 142-82-5)	15 minute	500 ppm
	8 hour	400 ppm
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	15 minute	500 ppm
	8 hour	400 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

**9. Physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Color</b>	Water-white.
<b>Odor</b>	Solvent.
<b>Melting point and freezing point</b>	-195.9 °F (-126.6 °C) estimated
<b>Boiling point or initial boiling point and boiling range</b>	132.8 °F (56 °C) estimated
<b>Flammability</b>	Not available.
<b>Lower and upper explosive limits</b>	
<b>Explosive limit - lower (%)</b>	1 % estimated
<b>Explosive limit - upper (%)</b>	12.8 % estimated
<b>Flash point</b>	-0.00004 °F (-17.8 °C) estimated
<b>Auto-ignition temperature</b>	539.6 °F (282 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not available.
<b>Kinematic viscosity</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Slightly soluble.
<b>Partition coefficient (n-octanol/water) (log value)</b>	Not available.
<b>Vapor pressure</b>	1518.9 hPa estimated
<b>Density and relative density</b>	0.69 estimated
<b>Relative vapor density</b>	>1 (air = 1)
<b>Particle characteristics</b>	Not available.
<b>Other information</b>	
<b>Percent volatile</b>	96.7 % estimated
<b>VOC</b>	59.5 %

---

**10. Stability and reactivity**

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Contact with incompatible materials.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

---

**11. Toxicological information****Information on likely routes of exposure**

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
---	---

**Information on toxicological effects****Acute toxicity** Not known.

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
Heavy Duty Silicone Lubricant - 212g		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	1454 mg/kg
<b>Inhalation</b>		
LC50	Rat	82064 ppm, 4 hours 14 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	3593 mg/kg
<b>Components</b>	<b>Species</b>	<b>Test Results</b>
acetone (CAS 67-64-1)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 15800 mg/kg
<b>Inhalation</b>		
LC50	Rat	76 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	5800 mg/kg
heptane, branched, cyclic and linear (CAS 426260-76-6)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 60 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 5.2000000000000002 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
n-heptane (CAS 142-82-5)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	103 mg/m3, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 5 mg/kg

Components	Species	Test Results
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 73.5 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 3000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>		
<b>ACGIH Carcinogens</b>		
acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
acetone (CAS 67-64-1)	Not classifiable as a human carcinogen.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

## 12. Ecological information

<b>Ecotoxicity</b>	Very toxic to aquatic life with long lasting effects.	
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.	
<b>Bioaccumulative potential</b>		
<b>Partition coefficient n-octanol / water (log Kow)</b>		
acetone	-0.24	
n-heptane	4.66	
<b>Bioconcentration factor (BCF)</b>		
naphtha (petroleum), hydrotreated light	10 - 2500	
<b>Mobility in soil</b>	No data available.	
<b>Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Empty container can be recycled. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

### TDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not assigned.
<b>Environmental hazards</b>	Yes, but exempt from the regulations.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not assigned.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.


### Other information

<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.


### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	-
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes, but exempt from the regulations.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### IATA



### IMDG; TDG



---

## 15. Regulatory information

### Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268  
Product Category: Lubricants, silicone-based multi-purpose lubricants that are not solid or semi-solid.

### Canada. Excluded VOCs. Guidelines for Volatile Organic Compounds in Consumer Products. CEPA 1999. Environment Canada, as amended

acetone (CAS 67-64-1)

### Controlled Drugs and Substances Act

Not regulated.

### Export Control List (CEPA 1999, Schedule 3)

Not listed.

### Greenhouse Gases

Not listed.

### Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

acetone (CAS 67-64-1)

### Precursor Control Regulations

acetone (CAS 67-64-1)

Class B

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
----------------------	----------------	------------------------

Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

## 16. Other information

### Issue date

12-12-2023

### Version #

01

### Further information

CRC # 519C/1002519

**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.