




1. Identification

Product identifier	QD™ Electronic Cleaner - 311 g	
Other means of identification		
Product Code	No. 75102 (Item# 1006344)	
Recommended use	Electronic cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	Distributor information	
Manufactured or sold by:		
Company name	CRC Canada Co.	
Address	83 Galaxy Blvd	
	Unit 35 - 37	
	Toronto, ON M9W 5X6	
	Canada	
Telephone		
General Information	416-847-7750	
Technical Assistance	800-556-5074	
24-Hour Emergency (CHEMTREC)	800-424-9300 (Canada)	
Website	crcindustries.ca	
2. Hazard identification		
Physical hazards	Aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
	Hazardous to the ozone layer	Category 1
Label elements		
	$\land \land \land \land$	



Danger

Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist/vapors. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
Storage	Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental information	None.
Other hazards	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	60 - 80
1,1-difluoroethane	HFC-152a	75-37-6	15 - 40

The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

	only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3
		400 ppm
Canada. New Brunswick OELs: 1	Threshold Limit Values (TLVs)	
	· · · ·	Based on the 1991 and 1997 ACGIH TLVs and BEIs
Publication (New Brunswick Reg	· · · ·	
Canada. New Brunswick OELs: 7 Publication (New Brunswick Reg Components naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	gulation 91-191)	Based on the 1991 and 1997 ACGIH TLVs and BEIs

Components	Туре	Value
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	525 mg/m3
Canada. Quebec OELs. (N Components	linistry of Labor - Regulation respecti Type	ng occupational health and safety) Value
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1000 mg/m3
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety Type	Regulations, 1996, Table 21) Value
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	15 minute	500 ppm
	8 hour	400 ppm
Biological limit values	No biological exposure limits noted	for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.	
•	s, such as personal protective equipr	
Eye/face protection	Wear safety glasses with side shield	ls (or goggles).
Skin protection Hand protection	Wear protective gloves such as: New	oprene. Nitrile. Viton/butyl.
Other	Wear appropriate chemical resistant	t clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	
9. Physical and chemica	Il properties	
Physical state	Liquid.	
Color	Colorless.	
Odor	Alcoholic.	

Not available.
137 °F (58.3 °C) estimated
Not available.
S
3.3 % estimated
19 % estimated
-0.00004 °F (-17.8 °C) estimated
550.4 °F (288 °C) estimated
Not available.
Not available.
Not available.

Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapor pressure	Not available.
Density and relative density	0.72 estimated
Relative vapor density	>1 (air = 1)
Particle characteristics	Not available.
Other information	
Percent volatile	100 % estimated
VOC	74.9 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Hydrocarbon fumes and smoke.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.


Product	Species	Test Results
QD™ Electronic Cleaner - 3	311 g	
<u>Acute</u>		
Inhalation		
LC50	Rat	14 mg/l, 4 Hours
Oral		
LD50	Rat	2626 mg/kg
Components	Species	Test Results
1,1-difluoroethane (CAS 75	5-37-6)	
<u>Acute</u>		
Inhalation		
LC50	Mouse	369000 ppm, 2 Hours
naphtha (petroleum), hydro	treated light (CAS 64742-49-0)	
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg

Components	Species	Test Results
Inhalation		
Vapor	-	
LC50	Rat	> 5.20000000000002 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Based on available data, the classification criteria are not met.	
Skin sensitization	Based on available data, the	e classification criteria are not met.
Germ cell mutagenicity	Based on available data, the	e classification criteria are not met.
Carcinogenicity	Not classifiable as to carcino criteria are not met.	ogenicity to humans. Based on available data, the classification
Reproductive toxicity	Suspected of damaging fert	lity or the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness or di	zziness.
Specific target organ toxicity - repeated exposure	Based on available data, the	e classification criteria are not met.
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be	e harmful.
12. Ecological information	n	
Ecotoxicity	Toxic to aquatic life with long lasting effects. Harms public health and the environment by destroying ozone in the upper atmosphere.	
Persistence and degradability		degradability of any ingredients in the mixture.
Bioaccumulative potential		
Partition coefficient n-octar 1,1-difluoroethane	nol / water (log Kow)	0.75
Bioconcentration factor (BC naphtha (petroleum), hydrotre		10 - 2500
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile potential.	e organic compounds which have a photochemical ozone creation
13. Disposal consideratio	ons	
Disposal instructions	container can be recycled. C sewers/water supplies. Do r	se in sealed containers at licensed waste disposal site. Empty Contents under pressure. Do not allow this material to drain into ot contaminate ponds, waterways or ditches with chemical or used hts/container in accordance with local/regional/national/international
Local disposal regulations	Dispose in accordance with	all applicable regulations.
Waste from residues / unused products		th local regulations. Empty containers or liners may retain some rial and its container must be disposed of in a safe manner (see:
Contaminated packaging	Since emptied containers m	ay retain product residue, follow label warnings even after container i should be taken to an approved waste handling site for recycling or
14. Transport information	1	
TDG		
UN number	UN1950	

UN number UN proper shipping name Transport hazard class(es)	UN1950 AEROSOLS, flammable, Limited Quantity
Class	2.1
Subsidiary risk	-

Packing group	Not assigned.
Environmental hazards	Yes, but exempt from the regulations.
	r Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
ERG Code	10L
Special precautions for use	r Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Packing group	
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for use	Read safety instructions, SDS and emergency procedures before handling.

ΙΑΤΑ



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268 Product Category: Electronics cleaner

Canada. Excluded VOCs. Guidelines for Volatile Organic Compounds in Consumer Products. CEPA 1999. Environment Canada, as amended

1,1-difluoroethane (CAS 75-37-6)

Controlled Drugs and Sub	stances Act	
Not regulated.		
Export Control List (CEPA	1999, Schedule 3)	
Not listed.		
Greenhouse Gases		
1,1-difluoroethane (CAS	,	
Precursor Control Regulat	ions	
Not regulated.		
International regulations		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable. Kyoto protocol		
1,1-difluoroethane (CAS Montreal Protocol	5 75-37-6) Listed.	
Not applicable.		
Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all comp	onents of this product comply with the inventory requirements administered by the gov	erning country(s)

"A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date Revision date Version # Further information	05-04-2020 10-16-2023 03 CRC # 985/1002984
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co
Revision information	This document has undergone significant changes and should be reviewed in its entirety.