



CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-08-07 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Heavy Duty Corrosion Inhibitor, 283 g
Product code : 1006415
Part number : 76026

1.2. Recommended use and restrictions on use

Recommended use : Corrosion inhibitor
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1

Extremely flammable aerosol. Pressurized container; may burst if heated.

Physical hazards not otherwise classified, Category 1

Skin corrosion/irritation, Category 2

Causes skin irritation.

Serious eye damage/eye irritation, Category 2B

Causes eye irritation.

Reproductive toxicity, Category 2

Suspected of damaging fertility or the unborn child.

Specific target organ toxicity – Single exposure, Category 3, Narcosis

May cause drowsiness or dizziness.

Aspiration hazard, Category 1

May be fatal if swallowed and enters airways.

Hazardous to the aquatic environment, Acute Hazard, Category 2

Toxic to aquatic life.

Hazardous to the aquatic environment, Chronic Hazard, Category 2

Toxic to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) :

Danger

Hazard statements (GHS CA) :

Extremely flammable aerosol
Pressurized container; may burst if heated

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA) : May be fatal if swallowed and enters airways
Causes skin and eye irritation
May cause drowsiness or dizziness
Suspected of damaging fertility or the unborn child
: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing vapors, spray, mist.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye and face protection.
Wash hands thoroughly after handling.
IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
Do NOT induce vomiting.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or a doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.
IF ON SKIN: Wash with plenty of water.
If skin irritation occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
IF exposed or concerned: Get medical advice or attention.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Petroleum gases, liquefied, sweetened	Petroleum gases, liquefied, sweetened	CAS-No.: 68476-86-8	15 – 40
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	10 – 30
Naphtha (petroleum), hydrotreated heavy	Naphtha (petroleum), hydrotreated heavy	CAS-No.: 64742-48-9	10 – 30
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	5 – 10
Dipropylene glycol methyl ether	Dipropylene glycol methyl ether	CAS-No.: 34590-94-8	1 – 5

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Name	Chemical name / Synonyms	Product identifier	%
Hexane	n-Hexane ; Hexane	CAS-No.: 110-54-3	0.5 – 1.5

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Remove ignition sources. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
- Personal Precautions, Protective Equipment and Emergency Procedures : Wear appropriate protective equipment and clothing during clean-up.

6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.
- Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not use if spray button is missing or defective. Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 3 Aerosol. Store locked up. Store in a well-ventilated place. Keep in fireproof place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Storage area : Store away from heat.

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum gases, liquefied, sweetened (68476-86-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Butane
VEMP (OEL TWAEV)	1900 mg/m ³ 800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm
Notations and remarks	Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
OEL TWAEV	1000 ppm
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Dipropylene glycol methyl ether (34590-94-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy) propanol (Dipropylene glycol methyl ether, DPGME)
OEL TWA	606 mg/m ³
	100 ppm
OEL STEL	909 mg/m ³
	150 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Dipropylene glycol monomethyl ether

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Dipropylene glycol methyl ether (34590-94-8)	
VECD (OEL STEV)	909 mg/m ³
	150 ppm
VEMP (OEL TWAEV)	606 mg/m ³
	100 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (bis-(2-Methoxypropyl) ether (DPGME))
OEL TWA	100 ppm
OEL STEL	150 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA	100 ppm
OEL STEL	150 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA	100 ppm
OEL STEL	150 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)propanol (DPGME)
OEL TWAEV	100 ppm
	150 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Dipropylene glycol methyl ether (34590-94-8)	
OEL TWA	100 ppm
OEL STEL	150 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Hexane (110-54-3)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	n-Hexane
VEMP (OEL TWA EV)	176 mg/m ³ 50 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	20 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexane (110-54-3)	
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWAEV	50 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexane (110-54-3)	
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Naphtha (petroleum), hydrotreated light (64742-49-0)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear fire/flammable resistant/retardant clothing.

Hand protection:

Wear protective gloves such as: Nitrile. Neoprene.

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Additional Regulatory Information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Dark amber
Odor	: Petroleum
Melting point	: -153.7 °C (-244.7 °F) estimated
Freezing point	: -153.7 °C (-244.7 °F) estimated
Boiling point	: 48 °C (118.4 °F) estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: No data available
Flash point	: < -17.8 °C (< 0 °F) estimated
Auto-ignition temperature	: 207 °C (404.6 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: Water: Negligible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: Fast
Density	: No data available
Relative density	: 0.72 estimated
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Aldehydes. Carbon oxides (CO, CO ₂). Ketones. Organic acids.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Petroleum gases, liquefied, sweetened (68476-86-8)	
LC50 Inhalation - Rat (Dust/Mist)	658 mg/l Source: IUCLID
Dipropylene glycol methyl ether (34590-94-8)	
LD50 oral rat	5660 mg/kg Source: ECHA
LD50 dermal rabbit	9510 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 3000 mg/m ³ Source: ECHA
Hexane (110-54-3)	
LD50 oral rat	24 ml/kg Source: ECHA
LD50 dermal rabbit	> 3350 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
LC50 Inhalation - Rat (Vapors)	259.354 mg/l Source: ECHA
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 23300 mg/l
Distillates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 5610 mg/l
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Distillates (petroleum), hydrotreated light	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Petroleum gases, liquefied, sweetened (68476-86-8)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Dipropylene glycol methyl ether (34590-94-8)	
NOAEL (oral, rat, 28 days)	919 mg/kg bw/day
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: other:
Hexane (110-54-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Dipropylene glycol methyl ether (34590-94-8)	
Viscosity, kinematic	3.905 mm ² /s
Naphtha (petroleum), hydrotreated light (64742-49-0)	
Viscosity, kinematic	0.67 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
Viscosity, kinematic	< 1 mm ² /s
Symptoms/effects	: May cause drowsiness or dizziness.

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Dipropylene glycol methyl ether (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	> 969 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 969 mg/l Source: ECHA
NOEC (chronic)	≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
LOEC (chronic)	0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
Hexane (110-54-3)	
LC50 - Fish [1]	> 1 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	50 mg/l waterflea
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LC50 - Fish [1]	> 3 mg/l
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	4.6 mg/l waterflea
EC50 - Other aquatic organisms [2]	10 mg/l
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Distillates (petroleum), hydrotreated light (64742-47-8)	
LC50 - Fish [1]	2.4 mg/l Source: ECOTOX
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
LC50 - Fish [1]	2200 mg/l Source: IUCLID
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea

12.2. Persistence and degradability

CRC® Heavy Duty Corrosion Inhibitor, 283 g	
Persistence and degradability	No data is available on the degradability of this product.

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Petroleum gases, liquefied, sweetened (68476-86-8)

Partition coefficient n-octanol/water (Log Pow) ≤ 2.8 Source: IUCLID

Dipropylene glycol methyl ether (34590-94-8)

Partition coefficient n-octanol/water (Log Pow) 0.0061

Hexane (110-54-3)

Partition coefficient n-octanol/water (Log Pow) 3.9 Source: ICSC

Naphtha (petroleum), hydrotreated light (64742-49-0)

Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID

Distillates (petroleum), hydrotreated light (64742-47-8)

Partition coefficient n-octanol/water (Log Pow) 3.3 – 6 Source: IUCLID

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Partition coefficient n-octanol/water (Log Pow) 2.1 – 6 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information




In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	IMDG	IATA
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No		

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® Heavy Duty Corrosion Inhibitor, 283 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Petroleum gases, liquefied, sweetened	68476-86-8	Listed on the Canadian DSL (Domestic Substances List)
Dipropylene glycol methyl ether	34590-94-8	Listed on the Canadian DSL (Domestic Substances List)
Hexane	110-54-3	Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), hydrotreated light	64742-47-8	Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Petroleum gases, liquefied, sweetened (68476-86-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Dipropylene glycol methyl ether (34590-94-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

CRC® Heavy Duty Corrosion Inhibitor, 283 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	79.2 %
Product Category	Not regulated.

SECTION 16: Other information

Issue date : 08-07-2025

Other information : CRC # 5224G-H/1002528-1002530.
Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.