



# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-07-14 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® Red Grease, 311 g  
Product code : 1750385

#### 1.2. Recommended use and restrictions on use

Recommended use : Lubricating grease  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Aerosol, Category 1

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Aspiration hazard, Category 1

Hazardous to the aquatic environment, Acute Hazard, Category 3

Hazardous to the aquatic environment, Chronic Hazard, Category 3

Extremely flammable aerosol. Pressurized container; may burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Hazard statements (GHS CA)

: Extremely flammable aerosol  
Pressurized container; may burst if heated  
May be fatal if swallowed and enters airways  
Causes skin irritation

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### Precautionary statements (GHS CA)

Causes serious eye irritation  
May cause drowsiness or dizziness  
: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing vapors, spray, mist.  
Use only outdoors or in a well-ventilated area.  
Wash hands thoroughly after handling.  
Wear protective gloves, eye and face protection.  
IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
Do NOT induce vomiting.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or a doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice or attention.  
IF ON SKIN: Wash with plenty of water.  
If skin irritation occurs: Get medical advice or attention.  
Take off contaminated clothing and wash it before reuse.  
Store locked up.  
Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container in accordance with local/regional/national regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
White mineral oil (petroleum)	White mineral oil (petroleum)	CAS-No.: 8042-47-5	30 – 60
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	10 – 30
Acetone	acetone, propan-2-one, propanone	CAS-No.: 67-64-1	10 – 30
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	5 – 10
Aluminum hydroxide benzoate stearate	ALUMINUM HYDROXIDE BENZOATE STEARATE	CAS-No.: 54326-11-3	5 – 10
Butane	Butane	CAS-No.: 106-97-8	1 – 5
Propane	Propane	CAS-No.: 74-98-6	1 – 5

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician immediately.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

#### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

#### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
- Personal Precautions, Protective Equipment and Emergency Procedures : Wear appropriate protective equipment and clothing during clean-up.

#### 6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
- Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 3 Aerosol. Store locked up. Store in a well-ventilated place. Keep in fireproof place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Butane (106-97-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Butane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Butane (106-97-8)</b>	
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Butane
VEMP (OEL TWAEV)	1900 mg/m <sup>3</sup>
	800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Butane, all isomers: n-butane
OEL STEL	1000 ppm
Notations and remarks	EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Butane
OEL STEL	2370 mg/m <sup>3</sup> (EX - Explosion hazard)
	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Butane
OEL STEL	2370 mg/m <sup>3</sup> (EX - Explosion hazard)
	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Butane
OEL STEL	2370 mg/m <sup>3</sup> (EX - Explosion hazard)
	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Butane, All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Butane (106-97-8)</b>	
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Butane, All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Butane, All isomers
OEL TWAEV	1000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Butane
OEL STEL	2370 mg/m <sup>3</sup> (EX - Explosion hazard) 1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Butane. All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Propane (74-98-6)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	Simple asphyxiant. EX
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Propane

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Propane (74-98-6)</b>	
Notations and remarks	Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Propane
Notations and remarks	TLV® Basis: Asphyxia

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Propane (74-98-6)</b>	
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
<b>Acetone (67-64-1)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Acetone

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
OEL TWA	1200 mg/m <sup>3</sup>
	500 ppm
OEL STEL	1800 mg/m <sup>3</sup>
	750 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Acetone
VECD (OEL STEV)	500 ppm
VEMP (OEL TWAEV)	250 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup>
	250 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	250 ppm
OEL STEL	500 ppm
Notations and remarks	eye irr; CNS impair; BEI
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup>
	250 ppm
OEL STEL	1187 mg/m <sup>3</sup>
	500 ppm

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup> 250 ppm
OEL STEL	1187 mg/m <sup>3</sup> 500 ppm
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWAEV	250 ppm 500 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	594 mg/m <sup>3</sup> 250 ppm
OEL STEL	1187 mg/m <sup>3</sup> 500 ppm

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA	500 ppm
OEL STEL	750 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

<b>White mineral oil (petroleum) (8042-47-5)</b>	
Occupational Exposure Limit	5 mg/mg <sup>3</sup> TLV (ACGIH)

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Nitrile. Neoprene.

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Red  
Odor : acetone-like  
Melting point : -94.7 °C (-138.5 °F) estimated  
Freezing point : -94.7 °C (-138.5 °F) estimated  
Boiling point : 35 °C (95 °F) estimated

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Flammability (solid, gas)	: Not applicable
Explosion limits	: No data available
Flash point	: < -5 °C (< 23 °F)
Auto-ignition temperature	: 210 °C (410 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: Water: Slightly soluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: Fast
Density	: 0.79 estimated
Relative density	: No data available
Relative vapor density at 20°C	: > 1 (air=1)
Particle characteristics	: No data available

### 9.2. Additional Regulatory Information

No additional information available

## SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Acrid smoke. Carbon oxides (CO, CO <sub>2</sub> ).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Butane (106-97-8)</b>	
LC50 Inhalation - Rat [ppm]	> 800000 ppm Source: ECHA
<b>Propane (74-98-6)</b>	
LC50 Inhalation - Rat [ppm]	800000 ppm Source: ECHA
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 23300 mg/l
<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg Source: ECHA

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA
<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
<b>Aluminum hydroxide benzoate stearate (54326-11-3)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
<b>Acetone</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male
<b>Distillates (petroleum), hydrotreated light</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
<b>Acetone (67-64-1)</b>	
NOAEL (oral, rat, 90 days)	900 mg/kg bw/day

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>White mineral oil (petroleum) (8042-47-5)</b>	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
Viscosity, kinematic	0.67 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract. Aspiration may cause pulmonary edema and pneumonitis.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

<b>Butane (106-97-8)</b>	
LC50 - Fish [1]	27.98 mg/l Source: QSAR
EC50 96h - Algae [1]	16.47 mg/l Source: QSAR
<b>Propane (74-98-6)</b>	
LC50 - Fish [1]	> 100 mg/l Source: IUCLID
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
LC50 - Fish [1]	> 3 mg/l
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	4.6 mg/l waterflea
EC50 - Other aquatic organisms [2]	10 mg/l
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>Acetone (67-64-1)</b>	
LC50 - Fish [1]	5540 mg/l Source: ECHA
EC50 - Crustacea [1]	12600 – 12700 mg/l
EC50 - Other aquatic organisms [1]	12600 mg/l waterflea
EC50 - Other aquatic organisms [2]	3400 mg/l

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Acetone (67-64-1)</b>	
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>White mineral oil (petroleum) (8042-47-5)</b>	
LC50 - Fish [1]	> 10000 mg/l Source: IUCLID
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LC50 - Fish [1]	2.4 mg/l Source: ECOTOX
<b>Aluminum hydroxide benzoate stearate (54326-11-3)</b>	
LC50 - Fish [1]	> 100 mg/l Source: ECHA
EC50 - Crustacea [1]	> 100 mg/l Source: ECHA

### 12.2. Persistence and degradability

<b>CRC® Red Grease, 311 g</b>	
Persistence and degradability	No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

<b>Butane (106-97-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.89 Source: ICSC
<b>Propane (74-98-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.36
<b>Naphtha (petroleum), hydrotreated light (64742-49-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
<b>Acetone (67-64-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0.23
<b>White mineral oil (petroleum) (8042-47-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	5.18 Source: Quantitative Structure Activity Relation
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
<b>Aluminum hydroxide benzoate stearate (54326-11-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.884 Source: ECHA

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)




### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Regional waste regulation	: Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information	: Do not re-use empty containers.

### SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
<b>14.1. UN number</b>		
UN1950	1950	1950
<b>14.2. Proper Shipping Name</b>		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
<b>14.3. Transport hazard class(es)</b>		
LTD QTY	LTD QTY	LTD QTY
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
No		

#### 14.6. Special precautions for user

<b>TDG</b>	
TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### CRC® Red Grease, 311 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Butane	106-97-8	Listed on the Canadian DSL (Domestic Substances List)
Propane	74-98-6	Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed on the Canadian DSL (Domestic Substances List)
Acetone	67-64-1	Listed on the Canadian DSL (Domestic Substances List)
White mineral oil (petroleum)	8042-47-5	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), hydrotreated light	64742-47-8	Listed on the Canadian DSL (Domestic Substances List)

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Aluminum hydroxide benzoate stearate	54326-11-3	Listed on the Canadian DSL (Domestic Substances List)
--------------------------------------	------------	---

### 15.2. International regulations

#### Butane (106-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### White mineral oil (petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Aluminum hydroxide benzoate stearate (54326-11-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

### 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content 24.9 %

Product Category Lubricants, multi-purpose lubricants that are not solid or semi-solid.

## SECTION 16: Other information

Issue date : 07-14-2025

Author Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

# CRC® Red Grease, 311 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

---

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.