



# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-03-18 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® Foaming Coil Cleaner, 510 g  
Product code : 1752305

#### 1.2. Recommended use and restrictions on use

Recommended use : Cleaner for air conditioning or refrigeration coils  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

|  |   |
|--|---|
| Aerosol, Category 3  | Pressurized container; may burst if heated.   |
| Skin corrosion/irritation, Category 1B                           | Causes severe skin burns and eye damage.  |
| Serious eye damage/eye irritation, Category 1                    | Causes serious eye damage.  |
| Specific target organ toxicity, Single exposure, Category 1      | Causes damage to organs (gastrointestinal tract, respiratory system).                   |
| Specific target organ toxicity, Repeated exposure, Category 2    | May cause damage to organs (respiratory system) through prolonged or repeated exposure. |
| Hazardous to the aquatic environment, Acute Hazard, Category 2   | Toxic to aquatic life.  |
| Hazardous to the aquatic environment, Chronic Hazard, Category 2 | Toxic to aquatic life with long lasting effects.  |

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : Pressurized container; may burst if heated  
Causes severe skin burns and eye damage  
Causes damage to organs (gastrointestinal tract, respiratory system).  
May cause damage to organs (respiratory system) through prolonged or repeated exposure.

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not eat, drink or smoke when using this product. Do not breathe vapors, spray, mist. Wash hands thoroughly after handling. Wear protective gloves, eye and face protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or a doctor. IF exposed or concerned: Call a POISON CENTER or a doctor. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name   | Chemical name / Synonyms  | Product identifier   | %       |
|--|---|----------------------|---------|
| Water  | Water   | CAS-No.: 7732-18-5   | 60 – 80 |
| Benzenesulfonic acid, dimethyl-, sodium salt (1:1)                         | Sodium xylenesulphonate   | CAS-No.: 1300-72-7   | 10 – 30 |
| Propane  | Propane   | CAS-No.: 74-98-6     | 1 – 5   |
| Butane   | Butane  | CAS-No.: 106-97-8    | 1 – 5   |
| 2-butoxyethanol; ethylene glycol monobutyl ether                           | 2-Butoxyethanol ; Ethylene glycol monobutyl ether                   | CAS-No.: 111-76-2    | 1 – 5   |
| α-(4-Nonylphenyl)-ω-hydroxypoly(oxy-1,2-ethanediyl), branched              | α-(4-Nonylphenyl)-ω-hydroxy poly(oxy-1,2-ethanediyl), branched      | CAS-No.: 127087-87-0 | 1 – 5   |
| Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-, branched | Branched α-(nonylphenyl)-ω-hydroxy poly(oxy-1,2-ethanediyl)         | CAS-No.: 68412-54-4  | 1 – 5   |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) | Sulfobutanedioic acid 1,4-bis(2-ethylhexyl)ester sodium salt        | CAS-No.: 577-11-7    | 1 – 5   |
| potassium hydroxide, caustic potash  | Potassium hydroxide   | CAS-No.: 1310-58-3   | 1 – 5   |
| disodium metasilicate  | Disodium metasilicate   | CAS-No.: 6834-92-0   | 1 – 5   |
| tetrasodium ethylene diamine tetraacetate                                  | Ethylenediaminetetraacetic acid tetrasodium salt ; Tetrasodium EDTA | CAS-No.: 64-02-8     | 1 – 5   |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Call a physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

First-aid measures general : Provide general supportive measures and treat symptomatically. Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Causes severe burns. Burning pain and severe corrosive skin damage.

Symptoms/effects after eye contact : Serious damage to eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

#### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Alcohol resistant foam. Dry powder. Carbon dioxide.

#### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.3. Specific hazards arising from the hazardous product

Fire hazard : Propellant is flammable.

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Eliminate every possible source of ignition. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
- Personal Precautions, Protective Equipment and Emergency Procedures : Use a self-contained breathing apparatus in confined spaces and for emergencies. Wear appropriate protective equipment and clothing during clean-up.

#### 6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
- Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. Exposure to high temperature may cause can to burst. For product usage instructions, see the product label.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 1 Aerosol. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Packaging materials : Store always product in container of same material as original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Propane (74-98-6)                               |                             |
|---|-----------------------------|
| Canada (Alberta) - Occupational Exposure Limits |                             |
| Local name                                      | Propane                     |
| OEL TWA   | 1000 ppm                    |
| Regulatory reference                            | Alberta Regulation 191/2021 |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>Propane (74-98-6)</b>   |  |
|--|--|
| <b>Canada (Quebec) - Occupational Exposure Limits</b>                    |  |
| Local name   | Propane  |
| Notations and remarks  | Simple asphyxiant. EX  |
| Regulatory reference   | S-2.1, r. 13 - Regulation respecting occupational health and safety  |
| <b>Canada (British Columbia) - Occupational Exposure Limits</b>          |  |
| Local name   | Propane  |
| Notations and remarks  | Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit) |
| Regulatory reference   | OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)   |
| <b>Canada (Manitoba) - Occupational Exposure Limits</b>                  |  |
| Local name   | Propane  |
| Notations and remarks  | TLV® Basis: Simple Asphyxiant  |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b> |  |
| Local name   | Propane  |
| Notations and remarks  | TLV® Basis: Simple Asphyxiant  |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nova Scotia) - Occupational Exposure Limits</b>               |  |
| Local name   | Propane  |
| Notations and remarks  | TLV® Basis: Simple Asphyxiant  |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nunavut) - Occupational Exposure Limits</b>                   |  |
| Local name   | Propane  |
| OEL TWA  | 1000 ppm   |
| OEL STEL   | 1250 ppm   |
| Regulatory reference   | Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)   |
| <b>Canada (Northwest Territories) - Occupational Exposure Limits</b>     |  |
| Local name   | Propane  |
| OEL TWA  | 1000 ppm   |
| OEL STEL   | 1250 ppm   |
| Regulatory reference   | Occupation Health and Safety Regulations R-039-2015 (R-090-2024)   |
| <b>Canada (Ontario) - Occupational Exposure Limits</b>                   |  |
| Local name   | Propane  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|  |   |
|--|---|
| <b>Propane (74-98-6)</b>   |   |
| Notations and remarks  | See Appendix F: Minimal Oxygen Content  |
| Regulatory reference   | Ontario Occupational Exposure Limits under Regulation 833   |
| <b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>      |   |
| Local name   | Propane   |
| Notations and remarks  | TLV® Basis: Simple Asphyxiant   |
| Regulatory reference   | ACGIH 2024  |
| <b>Canada (Saskatchewan) - Occupational Exposure Limits</b>              |   |
| Local name   | Propane   |
| OEL TWA  | 1000 ppm  |
| OEL STEL   | 1250 ppm  |
| Regulatory reference   | The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10   |
| <b>Butane (106-97-8)</b>   |   |
| <b>Canada (Alberta) - Occupational Exposure Limits</b>                   |   |
| Local name   | Butane  |
| OEL TWA  | 1000 ppm  |
| Regulatory reference   | Alberta Regulation 191/2021   |
| <b>Canada (Quebec) - Occupational Exposure Limits</b>                    |   |
| Local name   | Butane  |
| VEMP (OEL TWAEV)   | 1900 mg/m <sup>3</sup><br>800 ppm   |
| Regulatory reference   | S-2.1, r. 13 - Regulation respecting occupational health and safety   |
| <b>Canada (British Columbia) - Occupational Exposure Limits</b>          |   |
| Local name   | Butane, all isomers: n-butane   |
| OEL STEL   | 1000 ppm  |
| Notations and remarks  | EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit) |
| Regulatory reference   | OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)  |
| <b>Canada (Manitoba) - Occupational Exposure Limits</b>                  |   |
| Local name   | Butane  |
| OEL STEL   | 1000 ppm (EX - Explosion hazard)  |
| Notations and remarks  | TLV® Basis: CNS impair  |
| Regulatory reference   | ACGIH 2024  |
| <b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b> |   |
| Local name   | Butane  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|  |  |
|--|--|
| <b>Butane (106-97-8)</b>   |  |
| OEL STEL   | 1000 ppm (EX - Explosion hazard)   |
| Notations and remarks  | TLV® Basis: CNS impair   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nova Scotia) - Occupational Exposure Limits</b>           |  |
| Local name   | Butane   |
| OEL STEL   | 1000 ppm (EX - Explosion hazard)   |
| Notations and remarks  | TLV® Basis: CNS impair   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nunavut) - Occupational Exposure Limits</b>               |  |
| Local name   | Butane, All isomers  |
| OEL TWA  | 1000 ppm   |
| OEL STEL   | 1250 ppm   |
| Regulatory reference   | Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021) |
| <b>Canada (Northwest Territories) - Occupational Exposure Limits</b> |  |
| Local name   | Butane, All isomers  |
| OEL TWA  | 1000 ppm   |
| OEL STEL   | 1250 ppm   |
| Regulatory reference   | Occupation Health and Safety Regulations R-039-2015 (R-090-2024)                   |
| <b>Canada (Ontario) - Occupational Exposure Limits</b>               |  |
| Local name   | Butane, All isomers  |
| OEL TWAEV  | 1000 ppm   |
| Regulatory reference   | Ontario Occuational Exposure Limits under Regulation 833                           |
| <b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>  |  |
| Local name   | Butane   |
| OEL STEL   | 1000 ppm (EX - Explosion hazard)   |
| Notations and remarks  | TLV® Basis: CNS impair   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Saskatchewan) - Occupational Exposure Limits</b>          |  |
| Local name   | Butane. All isomers  |
| OEL TWA  | 1000 ppm   |
| OEL STEL   | 1250 ppm   |
| Regulatory reference   | The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10        |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b>       |   |
|--|---|
| <b>Canada (Alberta) - Occupational Exposure Limits</b>                   |   |
| Local name   | 2-Butoxyethanol (Ethylene glycol monobutyl ether)   |
| OEL TWA  | 97 mg/m <sup>3</sup><br>20 ppm  |
| Notations and remarks  | Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required. |
| Regulatory reference   | Alberta Regulation 191/2021   |
| <b>Canada (Quebec) - Occupational Exposure Limits</b>                    |   |
| Local name   | 2-Butoxyethanol (Butyl cellosolve®)   |
| VEMP (OEL TWAEV)   | 20 ppm  |
| Notations and remarks  | C3  |
| Regulatory reference   | S-2.1, r. 13 - Regulation respecting occupational health and safety   |
| <b>Canada (British Columbia) - Occupational Exposure Limits</b>          |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWA  | 20 ppm  |
| Regulatory reference   | OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)  |
| <b>Canada (Manitoba) - Occupational Exposure Limits</b>                  |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWA  | 20 ppm  |
| Notations and remarks  | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI                            |
| Regulatory reference   | ACGIH 2024  |
| <b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b> |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWA  | 20 ppm  |
| Notations and remarks  | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI                            |
| Regulatory reference   | ACGIH 2024  |
| <b>Canada (Nova Scotia) - Occupational Exposure Limits</b>               |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWA  | 20 ppm  |
| Notations and remarks  | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI                            |
| Regulatory reference   | ACGIH 2024  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|  |   |
|--|---|
| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b>   |   |
| <b>Canada (Nunavut) - Occupational Exposure Limits</b>               |   |
| Local name   | 2-Butoxyethanol (Butyl Cellosolve or EGBE)  |
| OEL TWA  | 20 ppm  |
| OEL STEL   | 30 ppm  |
| Regulatory reference   | Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)  |
| <b>Canada (Northwest Territories) - Occupational Exposure Limits</b> |   |
| Local name   | 2-Butoxyethanol (Butyl Cellosolve or EGBE)  |
| OEL TWA  | 20 ppm  |
| OEL STEL   | 30 ppm  |
| Regulatory reference   | Occupation Health and Safety Regulations R-039-2015 (R-090-2024)  |
| <b>Canada (Ontario) - Occupational Exposure Limits</b>               |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWAEV  | 20 ppm  |
| Regulatory reference   | Ontario Occuational Exposure Limits under Regulation 833  |
| <b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>  |   |
| Local name   | 2-Butoxyethanol (EGBE)  |
| OEL TWA  | 20 ppm  |
| Notations and remarks  | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI                            |
| Regulatory reference   | ACGIH 2024  |
| <b>Canada (Saskatchewan) - Occupational Exposure Limits</b>          |   |
| Local name   | 2-Butoxyethanol (Butyl Cellosolve or EGBE)  |
| OEL TWA  | 20 ppm  |
| OEL STEL   | 30 ppm  |
| Regulatory reference   | The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10   |
| <b>potassium hydroxide, caustic potash (1310-58-3)</b>               |   |
| <b>Canada (Alberta) - Occupational Exposure Limits</b>               |   |
| Local name   | Potassium hydroxide   |
| OEL C  | 2 mg/m <sup>3</sup>   |
| Notations and remarks  | Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required. |
| Regulatory reference   | Alberta Regulation 191/2021   |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|  |  |
|--|--|
| <b>potassium hydroxide, caustic potash (1310-58-3)</b>                   |  |
| <b>Canada (Quebec) - Occupational Exposure Limits</b>                    |  |
| Local name   | Potassium hydroxide  |
| Plafond (OEL C)  | 2 mg/m <sup>3</sup>  |
| Notations and remarks  | RP, EM   |
| Regulatory reference   | S-2.1, r. 13 - Regulation respecting occupational health and safety                |
| <b>Canada (British Columbia) - Occupational Exposure Limits</b>          |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Regulatory reference   | OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)         |
| <b>Canada (Manitoba) - Occupational Exposure Limits</b>                  |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Notations and remarks  | TLV® Basis: URT, eye, & skin irr   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b> |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Notations and remarks  | TLV® Basis: URT, eye, & skin irr   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nova Scotia) - Occupational Exposure Limits</b>               |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Notations and remarks  | TLV® Basis: URT, eye, & skin irr   |
| Regulatory reference   | ACGIH 2024   |
| <b>Canada (Nunavut) - Occupational Exposure Limits</b>                   |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Regulatory reference   | Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021) |
| <b>Canada (Northwest Territories) - Occupational Exposure Limits</b>     |  |
| Local name   | Potassium hydroxide  |
| OEL C  | 2 mg/m <sup>3</sup>  |
| Regulatory reference   | Occupation Health and Safety Regulations R-039-2015 (R-090-2024)                   |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>potassium hydroxide, caustic potash (1310-58-3)</b>              |   |
|---|---|
| <b>Canada (Ontario) - Occupational Exposure Limits</b>              |   |
| Local name  | Potassium hydroxide   |
| OEL C   | 2 mg/m <sup>3</sup>   |
| Regulatory reference  | Ontario Occupational Exposure Limits under Regulation 833                   |
| <b>Canada (Prince Edward Island) - Occupational Exposure Limits</b> |   |
| Local name  | Potassium hydroxide   |
| OEL C   | 2 mg/m <sup>3</sup>   |
| Notations and remarks   | TLV® Basis: URT, eye, & skin irr  |
| Regulatory reference  | ACGIH 2024  |
| <b>Canada (Saskatchewan) - Occupational Exposure Limits</b>         |   |
| Local name  | Potassium hydroxide   |
| OEL C   | 2 mg/m <sup>3</sup>   |
| Regulatory reference  | The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10 |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Materials for protective clothing:

Wear appropriate chemical resistant clothing.

#### Hand protection:

Wear protective gloves such as: Nitrile. Neoprene. Butyl rubber

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Light yellow

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|   |   |
|---|---|
| Odor  | : Glycol ether  |
| Melting point                                   | : -74.8 °C (-102.6 °F) estimated  |
| Freezing point                                  | : -74.8 °C (-102.6 °F) estimated  |
| Boiling point                                   | : 100 °C (212 °F) estimated   |
| Flammability (solid, gas)                       | : Not applicable  |
| Explosion limits                                | : Lower explosion limit: 2.6 % estimated<br>Upper explosion limit: 23.5 % estimated |
| Flash point                                     | : None.   |
| Auto-ignition temperature                       | : 238 °C (460,4 °F) estimated   |
| Decomposition temperature                       | : No data available   |
| pH  | : 13.3  |
| Viscosity, kinematic                            | : No data available   |
| Solubility                                      | : Water: Soluble  |
| Partition coefficient n-octanol/water (Log Pow) | : No data available   |
| Vapor pressure                                  | : 280.7 hPa estimated   |
| Evaporation rate                                | : Slow  |
| Density   | : No data available   |
| Relative density                                | : 1.09 estimated  |
| Relative vapor density at 20°C                  | : > 1 (air=1)   |
| Particle characteristics                        | : No data available   |

### 9.2. Additional Regulatory Information

No additional information available

## SECTION 10: Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : The product is non-reactive under normal conditions of use, storage and transport.   |
| Chemical stability                 | : Stable under normal conditions of use.   |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use.   |
| Conditions to avoid                | : High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.   |
| Incompatible materials             | : Acids. Strong oxidizing agents.  |
| Hazardous decomposition products   | : Aldehydes. Ammonia. Carbon oxides (CO, CO <sub>2</sub> ). Formaldehyde. Hydrogen cyanide. Ketones. Nitrogen oxides. Organic acids. Potassium oxides. Sulfur oxides (SO <sub>x</sub> ). |

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b> |                        |
|--|------------------------|
| LD50 oral  | 1746 mg/kg body weight |
| LD50 dermal  | 435 mg/kg body weight  |
| LC50 Inhalation - Rat (Dust/Mist)                                  | 2200 mg/l              |

| <b>α-(4-Nonylphenyl)-ω-hydroxypoly(oxy-1,2-ethanediyl), branched (127087-87-0)</b> |   |
|--|---|
| LD50 oral rat  | 1300 mg/kg  |
| LD50 oral  | 657.2 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: other., 95% CL: 265 - 1664,2 |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7)</b> |   |
|--|---|
| LD50 oral rat  | 1900 mg/kg Source: Corporate Solution From Thomson Micromedex   |
| LD50 dermal rabbit   | 10000 mg/kg Source: International Uniform Chemical Information Database   |
| LC50 Inhalation - Rat (Dust/Mist)  | 20000 mg/l  |
| <b>Benzenesulfonic acid, dimethyl-, sodium salt (1:1) (1300-72-7)</b>                        |   |
| LD50 oral rat  | > 5000 mg/kg Source: SIDS   |
| LD50 dermal rabbit   | ≥ 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)  |
| <b>potassium hydroxide, caustic potash (1310-58-3)</b>                                       |   |
| LD50 oral rat  | 273 mg/kg   |
| <b>disodium metasilicate (6834-92-0)</b>   |   |
| LD50 oral rat  | 1153 mg/kg  |
| LD50 dermal rat  | > 5000 mg/kg body weight Animal: rat, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)   |
| LC50 Inhalation - Rat  | > 2.06 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)  |
| <b>tetrasodium ethylene diamine tetraacetate (64-02-8)</b>                                   |   |
| LD50 oral rat  | 1700 – 1913 mg/kg Source: EU RAR  |
| Skin corrosion/irritation  | : Causes severe skin burns.<br>pH: 13.3   |
| Serious eye damage/irritation  | : Causes serious eye damage.<br>pH: 13.3  |
| Respiratory or skin sensitization  | : Not classified  |
| Germ cell mutagenicity   | : Not classified.   |
| Carcinogenicity  | : Not classified.   |
| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b>                           |   |
| IARC group   | 3 - Not classifiable  |
| <b>Benzenesulfonic acid, dimethyl-, sodium salt (1:1) (1300-72-7)</b>                        |   |
| NOAEL (chronic,oral,animal/female,2 years)   | ≥ 60 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Reproductive toxicity  | : Not classified  |
| <b>disodium metasilicate</b>   |   |
| NOAEL (animal/female, F0/P)  | > 159 mg/kg body weight Animal: rat, Animal sex: female   |
| STOT-single exposure   | : Causes damage to organs (gastrointestinal tract, respiratory system).   |
| STOT-repeated exposure   | : May cause damage to organs (respiratory system) through prolonged or repeated exposure.   |
| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b>                           |   |
| NOAEL (dermal,rat/rabbit,90 days)  | > 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)                            |
| STOT-repeated exposure   | May cause damage to organs through prolonged or repeated exposure.  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7)</b>   |  |
|--|--|
| NOAEL (oral, rat, 90 days)   | > 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| <b>Benzenesulfonic acid, dimethyl-, sodium salt (1:1) (1300-72-7)</b>                          |  |
| NOAEL (oral, rat, 90 days)   | 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)  |
| NOAEL (dermal, rat/rabbit, 90 days)  | 440 mg/kg bw/day   |
| <b>disodium metasilicate (6834-92-0)</b>   |  |
| NOAEL (oral, rat, 90 days)   | 227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)   |
| <b>tetrasodium ethylene diamine tetraacetate (64-02-8)</b>                                     |  |
| LOAEL (oral, rat, 90 days)   | 60 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)  |
| LOAEC (inhalation, rat, dust/mist/fume, 90 days)   | 0.015 mg/l air Animal: rat, Animal sex: female, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)   |
| NOAEL (oral, rat, 90 days)   | 6 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)   |
| STOT-repeated exposure   | Causes damage to organs through prolonged or repeated exposure.  |
| Aspiration hazard  | : Not classified   |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-, branched (68412-54-4)</b> |  |
| Viscosity, kinematic   | 241.279 mm <sup>2</sup> /s   |
| <b>potassium hydroxide, caustic potash (1310-58-3)</b>   |  |
| Viscosity, kinematic   | 1.252 mm <sup>2</sup> /s   |
| Symptoms/effects after inhalation  | : May cause drowsiness or dizziness. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Danger of serious damage to health by prolonged exposure through inhalation.                        |
| Symptoms/effects after skin contact  | : Causes severe burns. Burning pain and severe corrosive skin damage.  |
| Symptoms/effects after eye contact   | : Serious damage to eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.   |
| Symptoms/effects after ingestion   | : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.   |

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

| <b>Propane (74-98-6)</b> |                           |
|--------------------------|---------------------------|
| LC50 - Fish [1]          | > 100 mg/l Source: IUCLID |
| <b>Butane (106-97-8)</b> |                           |
| LC50 - Fish [1]          | 27.98 mg/l Source: QSAR   |
| EC50 96h - Algae [1]     | 16.47 mg/l Source: QSAR   |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

| <b>2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)</b>                             |   |
|--|---|
| LC50 - Fish [1]  | 1474 mg/l Source: ECHA  |
| EC50 - Crustacea [1]   | 1800 mg/l Source: ECHA  |
| EC50 - Other aquatic organisms [1]   | 1550 mg/l waterflea   |
| EC50 72h - Algae [1]   | 911 mg/l Source: ECHA   |
| NOEC chronic fish  | ≥ 100 mg/l Test organisms (species): <i>Oryzias latipes</i> Duration: '14 d'  |
| <b>α-(4-Nonylphenyl)-ω-hydroxypoly(oxy-1,2-ethanediyl), branched (127087-87-0)</b>             |   |
| LC50 - Fish [1]  | 84.7 mg/l Test organisms (species): <i>Lepomis macrochirus</i>  |
| EC50 - Crustacea [1]   | 14 mg/l Test organisms (species): <i>Daphnia magna</i>  |
| EC50 72h - Algae [1]   | 19.48545 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i> )   |
| EC50 96h - Algae [1]   | 12 mg/l Test organisms (species): other:  |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-, branched (68412-54-4)</b> |   |
| LC50 - Fish [1]  | 0.218 mg/l Test organisms (species): <i>Pimephales promelas</i>   |
| EC50 72h - Algae [1]   | > 3 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i> ) |
| NOEC chronic fish  | 0.006 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i> ) Duration: '91 d'                                       |
| NOEC (chronic)   | 0.1 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'  |
| <b>Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7)</b>   |   |
| LC50 - Fish [1]  | 28 mg/l Source: International Uniform Chemical Information Database   |
| EC50 - Crustacea [1]   | 36 mg/l Source: International Uniform Chemical Information Database   |
| <b>Benzenesulfonic acid, dimethyl-, sodium salt (1:1) (1300-72-7)</b>                          |   |
| LC50 - Fish [1]  | 656000 mg/l Source: ECOSAR  |
| EC50 - Crustacea [1]   | > 1020 mg/l Test organisms (species): <i>Daphnia magna</i>  |
| ErC50 algae  | > 230 mg/l  |
| EC50 96h - Algae [1]   | 270000 mg/l Source: ECOSAR  |
| <b>potassium hydroxide, caustic potash (1310-58-3)</b>   |   |
| LC50 - Fish [1]  | 80 mg/l   |
| EC50 - Crustacea [1]   | 660 mg/l  |
| ErC50 algae  | 1337 mg/l   |
| <b>disodium metasilicate (6834-92-0)</b>   |   |
| LC50 - Fish [1]  | 210 mg/l  |
| EC50 - Crustacea [1]   | 1700 mg/l Test organisms (species): <i>Daphnia magna</i>  |
| EC50 72h - Algae [1]   | 207 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i> )  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### tetrasodium ethylene diamine tetraacetate (64-02-8)

|                                    |  |
|------------------------------------|--|
| LC50 - Fish [1]                    | 41 mg/l Source: EPA  |
| EC50 - Crustacea [1]               | > 114 mg/l Test organisms (species): Daphnia magna               |
| EC50 - Other aquatic organisms [1] | 625 mg/l waterflea   |
| EC50 - Other aquatic organisms [2] | 2.77 mg/l  |
| EC50 72h - Algae [1]               | 100 mg/l Source: IUCLID  |
| NOEC chronic fish                  | ≥ 25.7 mg/l Test organisms (species): Duration: '35 d'           |
| LOEC (chronic)                     | 50 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

### 12.2. Persistence and degradability

#### CRC® Foaming Coil Cleaner, 510 g

|                               |  |
|-------------------------------|--|
| Persistence and degradability | No data is available on the degradability of this product. |
|-------------------------------|--|

### 12.3. Bioaccumulative potential

#### Propane (74-98-6)

|   |      |
|---|------|
| Partition coefficient n-octanol/water (Log Pow) | 2.36 |
|---|------|

#### Butane (106-97-8)

|   |                   |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 2.89 Source: ICSC |
|---|-------------------|

#### 2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

|   |                   |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 0.81 Source: ECHA |
|---|-------------------|

#### Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1) (577-11-7)

|   |                        |
|---|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 6.1 Source: ChemIDplus |
|---|------------------------|

#### Water (7732-18-5)

|   |       |
|---|-------|
| Partition coefficient n-octanol/water (Log Pow) | -1.38 |
|---|-------|

#### Benzenesulfonic acid, dimethyl-, sodium salt (1:1) (1300-72-7)

|   |                      |
|---|----------------------|
| Partition coefficient n-octanol/water (Log Pow) | -3.12 Source: GESTIS |
|---|----------------------|

#### potassium hydroxide, caustic potash (1310-58-3)

|   |      |
|---|------|
| Partition coefficient n-octanol/water (Log Pow) | 0.75 |
|---|------|

#### disodium metasilicate (6834-92-0)

|   |       |
|---|-------|
| Partition coefficient n-octanol/water (Log Pow) | -5.65 |
|---|-------|

#### tetrasodium ethylene diamine tetraacetate (64-02-8)

|   |                           |
|---|---------------------------|
| Partition coefficient n-octanol/water (Log Pow) | -13.17 Source: ChemIDplus |
|---|---------------------------|

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)



### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

|  |   |
|--|---|
| Regional waste regulation                  | : Dispose of contents/container in accordance with local/regional/national regulations.   |
| Waste treatment methods                    | : Dispose of contents/container in accordance with licensed collector's sorting instructions.                                     |
| Sewage disposal recommendations            | : Do not allow to enter sewers, surface or groundwater.   |
| Product/Packaging disposal recommendations | : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. |
| Additional information                     | : Contents under pressure.  |

### SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

| TDG  | IMDG  | IATA      |
|--|---|-----------|
| <b>14.1. UN number</b>   |   |           |
| UN1950   | 1950  | Forbidden |
| <b>14.2. Proper Shipping Name</b>  |   |           |
| Aerosols, non-flammable, containing substances in Class 8, Packing Group II (Limited quantity) | AEROSOLS (Limited quantity)   | Forbidden |
| <b>14.3. Transport hazard class(es)</b>  |   |           |
| LTD QTY  | LTD QTY   | Forbidden |
|             |  | Forbidden |
| <b>14.4. Packing group</b>   |   |           |
| Not applicable   | Not applicable  | Forbidden |
| <b>14.5. Environmental hazards</b>   |   |           |
| Marine Pollutant Exception   |   |           |

#### 14.6. Special precautions for user

|   |  |
|---|--|
| <b>TDG</b>  |  |
| TDG Primary Hazard Classes  | : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases   |
| UN-No. (TDG)  | : UN1950   |
| TDG Special Provisions  | : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment). |
| Explosive Limit and Limited Quantity Index                                  | : 1 L  |
| Excepted quantities (TDG)   | : E0   |
| Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index | : Forbidden  |
| Emergency Response Guide (ERG) Number                                       | : 126  |
| <b>IMDG</b>   |  |
| Class (IMDG)  | : 2.2 - Non-flammable, non-toxic gases   |
| Special provision (IMDG)  | : 63, 190, 277, 327, 344, 381, 959   |
| Limited quantities (IMDG)   | : SP277  |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

|                             |   |
|-----------------------------|---|
| Excepted quantities (IMDG)  | : E0  |
| Packing instructions (IMDG) | : P207, LP200   |
| Packing provisions (IMDG)   | : PP87, L2  |
| EmS-No. (Fire)              | : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES                             |
| EmS-No. (Spillage)          | : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) |
| Stowage category (IMDG)     | : None  |
| Stowage and handling (IMDG) | : SW1, SW22   |
| Segregation (IMDG)          | : SG69  |

### IATA

Forbidden

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### CRC® Foaming Coil Cleaner, 510 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

| Name   | CAS-No.     | Regulatory reference                                  |
|--|-------------|---|
| Propane  | 74-98-6     | Listed on the Canadian DSL (Domestic Substances List) |
| Butane   | 106-97-8    | Listed on the Canadian DSL (Domestic Substances List) |
| 2-butoxyethanol; ethylene glycol monobutyl ether                               | 111-76-2    | Listed on the Canadian DSL (Domestic Substances List) |
| $\alpha$ -(4-Nonylphenyl)- $\omega$ -hydroxypoly(oxy-1,2-ethanediyl), branched | 127087-87-0 | Listed on the Canadian DSL (Domestic Substances List) |
| Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-, branched     | 68412-54-4  | Listed on the Canadian DSL (Domestic Substances List) |
| Butanedioic acid, 2-sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (1:1)     | 577-11-7    | Listed on the Canadian DSL (Domestic Substances List) |
| Water  | 7732-18-5   | Listed on the Canadian DSL (Domestic Substances List) |
| Benzenesulfonic acid, dimethyl-, sodium salt (1:1)                             | 1300-72-7   | Listed on the Canadian DSL (Domestic Substances List) |
| potassium hydroxide, caustic potash  | 1310-58-3   | Listed on the Canadian DSL (Domestic Substances List) |
| disodium metasilicate  | 6834-92-0   | Listed on the Canadian DSL (Domestic Substances List) |
| tetrasodium ethylene diamine tetraacetate                                      | 64-02-8     | Listed on the Canadian DSL (Domestic Substances List) |

# CRC® Foaming Coil Cleaner, 510 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

|                  |                           |
|------------------|---------------------------|
| VOC content      | 15 %                      |
| Product Category | Single Purpose Degreaser. |

### SECTION 16: Other information

|                   |                      |
|-------------------|----------------------|
| Issue date        | : 03-18-2025         |
| Other information | : CRC # 781/1002792. |
| Author            | Joshua Weir          |

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.