



# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)  
Issue date: 2025-07-01 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name : CRC® Nickel Anti-Seize & Lubricating Compound, 226 g  
Product code : 1006137  
Part number : 72911

#### 1.2. Recommended use and restrictions on use

Recommended use : Anti-seize and lubricating compound  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Canada Co.  
83 Galaxy Blvd.  
Unit 35 - 37  
Toronto, ON M9W 5X6  
Canada  
T 416-847-7750  
[crcindustries.ca](http://crcindustries.ca)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)  
24-Hour Emergency

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Skin sensitization, Category 1  
Specific target organ toxicity, Repeated exposure, Category 1

May cause an allergic skin reaction.  
Causes damage to organs through prolonged or repeated exposure.

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : May cause an allergic skin reaction  
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS CA) : Do not eat, drink or smoke when using this product.  
Do not breathe dust, fume, vapors.  
Wear protective gloves.  
Wash hands thoroughly after handling.  
IF ON SKIN: Wash with plenty of water.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

If skin irritation or rash occurs: Get medical advice or attention.  
Take off contaminated clothing and wash it before reuse.  
Contaminated work clothing should not be allowed out of the workplace.  
Store away from incompatible materials  
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates (petroleum), solvent-refined heavy naphthenic	Distillates, petroleum, solvent-refined heavy naphthenic	CAS-No.: 64741-96-4	60 – 80
Graphite	Graphite	CAS-No.: 7782-42-5	10 – 30
Nickel	Nickel ; Raney nickel	CAS-No.: 7440-02-0	5 – 10
Aluminum	Aluminium	CAS-No.: 7429-90-5	1 – 5
Silica	Silicon dioxide	CAS-No.: 7631-86-9	1 – 5

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. If you feel unwell, seek medical advice.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water fog.

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.3. Specific hazards arising from the hazardous product

Fire hazard : No fire hazard.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.  
Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.  
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe vapors, fume. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.  
For product usage instructions, see the product label.  
Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Protect from sunlight.
Packaging materials	: Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Aluminum (7429-90-5)	
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Aluminum and its compounds
VEMP (OEL TWAEV)	5 mg/m <sup>3</sup> Rd
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Aluminum metal and insoluble compounds
OEL TWA	1 mg/m <sup>3</sup> Respirable
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Aluminum metal
OEL TWA	1 mg/m <sup>3</sup>
Notations and remarks	Pneumoconiosis; LRT irr
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Aluminum and compounds (as Al): Pyro powders
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Aluminum and compounds (as Al): Pyro powders
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Aluminum metal and insoluble compounds
OEL TWAEV	1 mg/m <sup>3</sup> (R - Respirable fraction)

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Aluminum (7429-90-5)</b>	
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Aluminum and compounds (as Al): Pyro powders
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Graphite (7782-42-5)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Graphite (all forms except graphite fibres)
OEL TWA	2 mg/m <sup>3</sup> respirable
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Graphite (all forms except fibers)
VEMP (OEL TWA <sub>EV</sub> )	2 mg/m <sup>3</sup> Rd
Notations and remarks	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Graphite - All forms except graphite fibres
OEL TWA	2 mg/m <sup>3</sup> Respirable
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Graphite
OEL TWA	2 mg/m <sup>3</sup>
Notations and remarks	Pneumoconiosis
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Graphite, natural-all forms except graphite fibres
OEL TWA	2 mg/m <sup>3</sup> (respirable fraction)
OEL STEL	4 mg/m <sup>3</sup> (respirable fraction)
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Graphite, natural-all forms except graphite fibres

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Graphite (7782-42-5)</b>	
OEL TWA	2 mg/m <sup>3</sup> (respirable fraction)
OEL STEL	4 mg/m <sup>3</sup> (respirable fraction)
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Graphite (all forms except graphite fibers)
OEL TWAEV	2 mg/m <sup>3</sup> (R - Respirable fraction)
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Graphite, natural-all forms except graphite fibres
OEL TWA	2 mg/m <sup>3</sup> (respirable fraction)
OEL STEL	4 mg/m <sup>3</sup> (respirable fraction)
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Nitrile

#### Eye protection:

Wear safety glasses with side shields (or goggles).

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: Silver
Odor	: Petroleum
Melting point	: 660 °C (1220 °F) estimated
Freezing point	: No data available
Boiling point	: 360 °C (680 °F) estimated
Flammability (solid, gas)	: Non flammable.
Explosion limits	: Not applicable
Flash point	: 218.3 °C (425 °F) Cleveland Open Cup
Auto-ignition temperature	: 260 °C (500 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: Not applicable
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: No data available
Density	: No data available
Relative density	: 1.18
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

#### 9.2. Additional Regulatory Information

No additional information available

### SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO <sub>2</sub> ). Silicone dioxide. Metal oxides.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified.

#### Aluminum (7429-90-5)

LD50 oral rat	> 15900 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 0.888 mg/l Source: ECHA

#### Nickel (7440-02-0)

LD50 oral rat	> 9000 mg/kg Source: NITE
---------------	---------------------------

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Graphite (7782-42-5)</b>	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 2000 mg/l Source: ECHA
<b>Distillates (petroleum), solvent-refined heavy naphthenic (64741-96-4)</b>	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l Source: IUCLID
<b>Silica (7631-86-9)</b>	
LD50 oral rat	3160 mg/kg Source: TOMES; HAZARDTEXT
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
<b>Nickel (7440-02-0)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
<b>Silica (7631-86-9)</b>	
NOAEL (chronic,oral,animal/male,2 years)	1800 – 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (chronic,oral,animal/female,2 years)	1800 – 3200 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
<b>Aluminum</b>	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
<b>Aluminum (7429-90-5)</b>	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic,oral,animal/male,90 days)	1034 mg/kg body weight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	1087 mg/kg body weight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Graphite (7782-42-5)</b>	
NOAEL (oral, rat, 90 days)	≥ 10000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
<b>Distillates (petroleum), solvent-refined heavy naphthenic (64741-96-4)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>Silica (7631-86-9)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 10000 mg/kg body weight Animal: rabbit

Aspiration hazard : Not classified

<b>CRC® Nickel Anti-Seize &amp; Lubricating Compound, 226 g</b>	
Viscosity, kinematic	Not applicable
Symptoms/effects after inhalation	: None under normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>Aluminum (7429-90-5)</b>	
EC50 - Other aquatic organisms [1]	> 100 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 100 mg/l
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
<b>Nickel (7440-02-0)</b>	
LC50 - Fish [1]	1.1 mg/l Source: OECD
<b>Graphite (7782-42-5)</b>	
LC50 - Fish [1]	100 mg/l Source: ECHA
EC50 72h - Algae [1]	19 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	7.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	47 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

<b>Distillates (petroleum), solvent-refined heavy naphthenic (64741-96-4)</b>	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
<b>Silica (7631-86-9)</b>	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
LOEC (chronic)	149.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

<b>CRC® Nickel Anti-Seize &amp; Lubricating Compound, 226 g</b>	
Persistence and degradability	No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

<b>Distillates (petroleum), solvent-refined heavy naphthenic (64741-96-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
<b>Silica (7631-86-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.53

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation	: Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
<b>14.1. UN number</b>		
Not regulated.	Not regulated.	Not regulated.

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	IMDG	IATA
<b>14.2. Proper Shipping Name</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.3. Transport hazard class(es)</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.4. Packing group</b>		
Not regulated.	Not regulated.	Not regulated.
<b>14.5. Environmental hazards</b>		
No supplementary information available		

### 14.6. Special precautions for user

#### TDG

Not regulated.

:

#### IMDG

Not regulated.

:

#### IATA

Not regulated.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Aluminum	7429-90-5	Listed on the Canadian DSL (Domestic Substances List)
Nickel	7440-02-0	Listed on the Canadian DSL (Domestic Substances List)
Graphite	7782-42-5	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	Listed on the Canadian DSL (Domestic Substances List)
Silica	7631-86-9	Listed on the Canadian DSL (Domestic Substances List)

# CRC® Nickel Anti-Seize & Lubricating Compound, 226 g

## Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

### 15.2. International regulations

#### Aluminum (7429-90-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Nickel (7440-02-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Graphite (7782-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Distillates (petroleum), solvent-refined heavy naphthenic (64741-96-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Silica (7631-86-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	0 %
Product Category	Lubricants, non-aerosol anti-seize lubricant

## SECTION 16: Other information

Issue date : 07-01-2025

Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.