



CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-04-30 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Water Based Silicone, 368 g
Product code : 1006147
Part number : 73035

1.2. Recommended use and restrictions on use

Recommended use : Silicone-based multi-purpose lubricant
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 3 Pressurized container; may burst if heated.

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : Pressurized container; may burst if heated

Precautionary statements (GHS CA) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.

Wear protective gloves, eye and face protection.

Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Water	Water	CAS-No.: 7732-18-5	65 – 85
White mineral oil (petroleum)	White mineral oil (petroleum)	CAS-No.: 8042-47-5	10 – 30
Petroleum gases, liquefied, sweetened	Petroleum gases, liquefied, sweetened	CAS-No.: 68476-86-8	7 – 13

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a poison center/doctor/physician if you feel unwell.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Propellant is flammable.

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures : Self-contained breathing apparatus.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
Hygiene measures : Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Level 1 Aerosol. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Butane
VEMP (OEL TWAEV)	1900 mg/m ³ 800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm
Notations and remarks	Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
OEL TWAEV	1000 ppm
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

White mineral oil (petroleum) (8042-47-5)	
Occupational Exposure Limit	5 mg/mg ³ TLV (ACGIH)

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Butyl rubber. Neoprene.

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Eye protection:

Wear safety glasses with side shields (or goggles).

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Hazy white
Odor	: Mild odor mineral oil
Melting point	: -60 °C (-76 °F) estimated
Freezing point	: -60 °C (-76 °F) estimated
Boiling point	: -100 °C (212 °F) estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: No data available
Flash point	: None (Tag Closed Cup)
Auto-ignition temperature	: 325 °C (617 °F) estimated
Decomposition temperature	: No data available
pH	: 10.7
Viscosity, kinematic	: No data available
Solubility	: Water: Dispersible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: Slow
Density	: No data available
Relative density	: 0.94 estimated
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO ₂). Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Acute toxicity (inhalation) : Not classified

Petroleum gases, liquefied, sweetened (68476-86-8)

LC50 Inhalation - Rat (Dust/Mist)	658 mg/l Source: IUCLID
-----------------------------------	-------------------------

White mineral oil (petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg Source: International Uniform Chemical Information Database
---------------	--

LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	--

LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
-----------------------	---

Water (7732-18-5)

LD50 oral rat	90000 mg/kg
---------------	-------------

LD50 dermal	> 90000 mg/kg body weight
-------------	---------------------------

Skin corrosion/irritation : Not classified
pH: 10.7

Serious eye damage/irritation : Not classified
pH: 10.7

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Petroleum gases, liquefied, sweetened (68476-86-8)

LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
---------------------------------------	---

White mineral oil (petroleum) (8042-47-5)

NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
----------------------------	---

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

White mineral oil (petroleum) (8042-47-5)

LC50 - Fish [1]	> 10000 mg/l Source: IUCLID
-----------------	-----------------------------

12.2. Persistence and degradability

CRC® Water Based Silicone, 368 g

Persistence and degradability	No data is available on the degradability of this product.
-------------------------------	--

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Petroleum gases, liquefied, sweetened (68476-86-8)

Partition coefficient n-octanol/water (Log Pow) ≤ 2.8 Source: IUCLID

White mineral oil (petroleum) (8042-47-5)

Partition coefficient n-octanol/water (Log Pow) 5.18 Source: Quantitative Structure Activity Relation

Water (7732-18-5)

Partition coefficient n-octanol/water (Log Pow) -1.38

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified




SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS	AEROSOLS (Limited quantity)	Aerosols, non-flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No supplementary information available		

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	: 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Class (IMDG)	: 2.2 - Non-flammable, non-toxic gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.2 - Gases : Non-flammable, Non-toxic
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A98, A145, A167, A802
ERG code (IATA)	: 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® Water Based Silicone, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

CRC® Water Based Silicone, 368 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Petroleum gases, liquefied, sweetened	68476-86-8	Listed on the Canadian DSL (Domestic Substances List)
White mineral oil (petroleum)	8042-47-5	Listed on the Canadian DSL (Domestic Substances List)
Water	7732-18-5	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Petroleum gases, liquefied, sweetened (68476-86-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

White mineral oil (petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	10.7 %
Product Category	Lubricants, silicone-based multi-purpose lubricants that are not solid or semi-solid

SECTION 16: Other information

Issue date	: 04-30-2025
Other information	: CRC # 696A/1002742.
Author	Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.