



CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-06-12 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Engine Stor™ Fogging Oil, 368 g
Product code : 1006297
Part number : 75027

1.2. Recommended use and restrictions on use

Recommended use : Fogging Fluid
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1

Extremely flammable aerosol. Pressurized container; may burst if heated.

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) :

Danger

Hazard statements (GHS CA) :

Extremely flammable aerosol
Pressurized container; may burst if heated

Precautionary statements (GHS CA) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national regulations.

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Distillates (petroleum), hydrotreated heavy naphthenic	Distillates (petroleum), hydrotreated heavy naphthenic	CAS-No.: 64742-52-5	15 – 40
Paraffin oils (petroleum), catalytic dewaxed heavy	Paraffin oils (petroleum), catalytic dewaxed heavy	CAS-No.: 64742-70-7	10 – 30
Paraffin oils (petroleum), catalytic dewaxed light	Paraffin oils (petroleum), catalytic dewaxed light	CAS-No.: 64742-71-8	7 – 13
Petroleum gases, liquefied, sweetened	Petroleum gases, liquefied, sweetened	CAS-No.: 68476-86-8	7 – 13
Butyl stearate	Octadecanoic acid butyl ester ; Butyl stearate	CAS-No.: 123-95-5	5 – 10
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	5 – 10
Petrolatum	Petrolatum	CAS-No.: 8009-03-8	1 – 5
Fatty acids, C18-unsatd., dimers	Unsatd. (C=18) fatty acids dimers	CAS-No.: 61788-89-4	1 – 5
Vanilla fragrances	-	CAS-No.: Proprietary	0.1 – 1
Water	Water	CAS-No.: 7732-18-5	0 – 0.1

Comments

: The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice.

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water fog. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures	: Wear appropriate protective equipment and clothing during clean-up.

6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 3 Aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep in fireproof place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum gases, liquefied, sweetened (68476-86-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Butane
VEMP (OEL TWA _{EV})	1900 mg/m ³ 800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm
Notations and remarks	Simple asphyxiant. EX (the substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
OEL TWAEV	1000 ppm
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petroleum gases, liquefied, sweetened (68476-86-8)	
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Neoprene. Nitrile

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Amber
Odor : Petroleum
Melting point : -20.6 °C (-5 °F) estimated
Freezing point : -20.6 °C (-5 °F) estimated
Boiling point : 100 °C (212 °F) estimated
Flammability (solid, gas) : Not applicable
Explosion limits : No data available
Flash point : > 176.7 °C (> 350 °F) estimated
Auto-ignition temperature : 260 °C (500 °F) estimated
Decomposition temperature : No data available
pH : No data available
Viscosity, kinematic : No data available
Solubility : Water: Negligible
Partition coefficient n-octanol/water (Log Pow) : No data available
Vapor pressure : No data available
Evaporation rate : No data available

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Density	: No data available
Relative density	: 0.86 estimated
Relative vapor density at 20°C	: > 1 (air=1)
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Aldehydes. Carbon oxides (CO, CO ₂). Ketones.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	5.53 mg/l Source: ECHA
Butyl stearate (123-95-5)	
LD50 oral rat	32000 mg/kg Source: THOMSON
Petrolatum (8009-03-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	3600 mg/kg Source: International Uniform Chemical Information Database
Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)	
LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 2.18 mg/l Source: ECHA
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Water (7732-18-5)	
LD50 oral rat	90000 mg/kg
LD50 dermal	> 90000 mg/kg body weight
Fatty acids, C18-unsatd., dimers (61788-89-4)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Petroleum gases, liquefied, sweetened (68476-86-8)	
LC50 Inhalation - Rat (Dust/Mist)	658 mg/l Source: IUCLID
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
Fatty acids, C18-unsatd., dimers	
NOAEL (animal/male, F0/P)	≥ 1450 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
NOAEL (animal/female, F0/P)	≥ 1692 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified.
Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Petrolatum (8009-03-8)	
LOAEL (dermal,rat/rabbit,90 days)	200 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (dermal,rat/rabbit,90 days)	≥ 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Petroleum gases, liquefied, sweetened (68476-86-8)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Butyl stearate (123-95-5)	
LC50 - Fish [1]	0.004 mg/l Source: ECOSAR
EC50 96h - Algae [1]	0.000414 mg/l Source: ECOSAR

Petrolatum (8009-03-8)	
LC50 - Fish [1]	0.0000009 mg/l Source: Quantitative Structure Activity Relation
EC50 96h - Algae [1]	0.0000022 mg/l Source: Quantitative Structure Activity Relation

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Fatty acids, C18-unsatd., dimers (61788-89-4)	
LC50 - Fish [1]	0.782 mg/l Source: Ecological Structure Activity Relationships
EC50 96h - Algae [1]	0.836 mg/l Source: Ecological Structure Activity Relationships

12.2. Persistence and degradability

CRC® Engine Stor™ Fogging Oil, 368 g	
Persistence and degradability	No data is available on the degradability of this product.

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Butyl stearate (123-95-5)	
Partition coefficient n-octanol/water (Log Pow)	9.7 Source: ChemIDplus
Petrolatum (8009-03-8)	
Partition coefficient n-octanol/water (Log Pow)	6 Source: International Chemical Safety Cards
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Water (7732-18-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.38
Petroleum gases, liquefied, sweetened (68476-86-8)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information




In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	IMDG	IATA
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No		

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® Engine Stor™ Fogging Oil, 368 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Listed on the Canadian DSL (Domestic Substances List)
Butyl stearate	123-95-5	Listed on the Canadian DSL (Domestic Substances List)
Petrolatum	8009-03-8	Listed on the Canadian DSL (Domestic Substances List)
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	Listed on the Canadian DSL (Domestic Substances List)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Listed on the Canadian DSL (Domestic Substances List)
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	Listed on the Canadian DSL (Domestic Substances List)
Water	7732-18-5	Listed on the Canadian DSL (Domestic Substances List)
Fatty acids, C18-unsatd., dimers	61788-89-4	Listed on the Canadian DSL (Domestic Substances List)
Petroleum gases, liquefied, sweetened	68476-86-8	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Butyl stearate (123-95-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

CRC® Engine Stor™ Fogging Oil, 368 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Petrolatum (8009-03-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Paraffin oils (petroleum), catalytic dewaxed light (64742-71-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Fatty acids, C18-unsatd., dimers (61788-89-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Petroleum gases, liquefied, sweetened (68476-86-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Vanilla fragrances (Proprietary)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	10.98 %
Product Category	Not regulated.

SECTION 16: Other information

Issue date	: 06-12-2025
Other information	: CRC # 537B/1002548.
Author	Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.