CRC® Ice-Off™ Windshield Spray De-Icer, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-03-18 Revision date: 2025-07-28 Supersedes: 2025-03-18 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Ice-Off™ Windshield Spray De-Icer, 340 g
Product code : 1006379
Part number : 75346

1.2. Recommended use and restrictions on use

Recommended use : Melt ice on windshields
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:
CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container; may burst if heated.
Acute toxicity (oral), Category 3	Toxic if swallowed.
Acute toxicity (dermal), Category 3	Toxic in contact with skin.
Acute toxicity (inhalation:vapor), Category 3	Toxic if inhaled.
Specific target organ toxicity, Single exposure, Category 1	Causes damage to organs (central nervous system, eyes).

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :

Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : Extremely flammable aerosol
Pressurized container; may burst if heated
Toxic if swallowed, in contact with skin or if inhaled
Causes damage to organs (central nervous system, eyes).

Precautionary statements (GHS CA) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.
Do not eat, drink or smoke when using this product.
Do not breathe vapors, spray, mist.
Use only outdoors or in a well-ventilated area.
Wash hands thoroughly after handling.
Wear protective gloves, protective clothing, eye and face protection.
IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
Rinse mouth.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or a doctor.
IF ON SKIN: Wash with plenty of water.
Take off immediately all contaminated clothing and wash it before reuse.
Call a POISON CENTER or a doctor if you feel unwell.
IF exposed or concerned: Call a POISON CENTER or a doctor.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Methanol	Methanol ; Methyl alcohol	CAS-No.: 67-56-1	80 – 100
Carbon dioxide	Carbon dioxide	CAS-No.: 124-38-9	5 – 10
Water	Water	CAS-No.: 7732-18-5	1 – 5

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret.
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Immediately call a poison center or doctor/physician. Do not give mouth-to-mouth resuscitation if victim ingested or inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

First-aid measures after skin contact : Wash skin with plenty of water. Remove/Take off immediately all contaminated clothing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after eye contact	:	Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after ingestion	:	Immediately call a poison center or doctor/physician. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Give water to drink if victim completely conscious/alert. Never give anything by mouth to an unconscious person. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
First-aid measures general	:	Call a physician immediately. Take off immediately all contaminated clothing. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Even small amounts (30-250 ml methanol) may be fatal. Symptoms are stomach ache, nausea, vomiting, dullness, visual disorder and blindness.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	:	Toxic if inhaled. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	:	Toxic in contact with skin.
Symptoms/effects after eye contact	:	Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	:	Toxic if swallowed. If swallowed there is a risk of blindness.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	:	Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	:	Water fog. Dry powder. Alcohol resistant foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	:	Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard	:	Extremely flammable aerosol.
Explosion hazard	:	Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	:	Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	:	Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Evacuate unnecessary personnel. Stop leak if safe to do so. Eliminate every possible source of ignition. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures	:	Use a self-contained breathing apparatus in confined spaces and for emergencies. Wear appropriate protective equipment and clothing during clean-up.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Exposure to high temperature may cause can to burst. Pressurized container: Do not pierce or burn, even after use. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not use if spray button is missing or defective. Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Level 3 Aerosol. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a cool, dry place out of direct sunlight.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m³
	5000 ppm
OEL STEL	54000 mg/m³
	30000 ppm
Regulatory reference	Alberta Regulation 191/2021

Carbon dioxide (124-38-9)	
Canada (Quebec) - Occupational Exposure Limits	
Local name	Carbon dioxide
VECD (OEL STEV)	54000 mg/m³
	30000 ppm
VEMP (OEL TWAEV)	9000 mg/m³
	5000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	15000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m³
	5000 ppm
OEL STEL	54000 mg/m³
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m³
	5000 ppm
OEL STEL	54000 mg/m³
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m³
	5000 ppm
OEL STEL	54000 mg/m³
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia

Carbon dioxide (124-38-9)	
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWAEV	5000 ppm
	30000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m³
	5000 ppm
OEL STEL	54000 mg/m³
	30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

Methanol (67-56-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Methanol (Methyl alcohol)
OEL TWA	262 mg/m³

Methanol (67-56-1)	
	200 ppm
OEL STEL	328 mg/m³
	250 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Methyl alcohol (Methanol)
VECD (OEL STEV)	328 mg/m³
	250 ppm
VEMP (OEL TWAEV)	262 mg/m³
	200 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m³
	200 ppm
OEL STEL	328 mg/m³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Headache; eye dam; dizziness; nausea

Methanol (67-56-1)	
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m³
	200 ppm
OEL STEL	328 mg/m³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m³
	200 ppm
OEL STEL	328 mg/m³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Methanol
OEL TWAEV	200 ppm
	250 ppm
Notations and remarks	Skin

Methanol (67-56-1)	
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m³
	200 ppm
OEL STEL	328 mg/m³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Wear protective gloves such as: Nitrile. Rubber.

Eye protection:
Wear safety glasses with side shields (or goggles).

Respiratory protection:
If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	Colorless
Odor	:	Pungent
Melting point	:	-97.8 °C (-144 °F) estimated
Freezing point	:	-97.8 °C (-144 °F) estimated
Boiling point	:	64.7 °C (148.5 °F) estimated
Flammability (solid, gas)	:	Not applicable
Explosion limits	:	Lower explosion limit: 2.6 % estimated Upper explosion limit: 36 % estimated
Flash point	:	12.2 °C (54 °F) Setaflash
Auto-ignition temperature	:	385 °C (725 °F) estimated
Decomposition temperature	:	No data available
pH	:	No data available
Viscosity, kinematic	:	No data available
Solubility	:	soluble in water. Water: completely soluble
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Vapor pressure	:	No data available
Evaporation rate	:	Fast
Density	:	No data available
Relative density	:	0.81 Concentrate
Relative vapor density at 20°C	:	1.1
Particle characteristics	:	No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	:	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	:	Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	:	No dangerous reactions known under normal conditions of use.
Conditions to avoid	:	High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	:	Combustible materials. Strong oxidizing agents.
Hazardous decomposition products	:	Carbon oxides (CO, CO2). Formaldehyde.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Toxic if swallowed.
Acute toxicity (dermal)	:	Toxic in contact with skin.
Acute toxicity (inhalation)	:	Inhalation:vapor: Toxic if inhaled.

Methanol (67-56-1)	
LD50 oral rat	100 mg/kg Source: National Institute of Environmental Research NCIS
LD50 dermal rabbit	300 mg/kg Source: ECHA
LD50 dermal	15800 mg/kg body weight

Water (7732-18-5)	
LD50 oral rat	90000 mg/kg
LD50 oral	> 90000 mg/kg body weight
LD50 dermal	> 90000 mg/kg body weight

Skin corrosion/irritation : Not classified

Methanol (67-56-1)	
pH	12.1 Source: Gestis

Serious eye damage/irritation : Not classified

Carbon dioxide	
pH	3.2 Source: HSDB

Methanol (67-56-1)	
pH	12.1 Source: Gestis

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs (central nervous system, eyes).

STOT-repeated exposure : Not classified

Methanol (67-56-1)	
NOAEC (inhalation, rat, 28 days)	6.66 mg/l
NOAEC (inhalation, rat, 90 days)	1.06 mg/l

Aspiration hazard : Not classified

Methanol (67-56-1)	
Viscosity, kinematic	0.692 mm²/s

Symptoms/effects after inhalation : Toxic if inhaled. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Toxic in contact with skin.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : Toxic if swallowed. If swallowed there is a risk of blindness.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Carbon dioxide (124-38-9)	
LC50 - Fish [1]	35 mg/l Source: HSDB

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l Source: ECHA
EC50 - Crustacea [1]	> 1000 mg/l
EC50 - Other aquatic organisms [1]	10000 mg/l waterflea

Methanol (67-56-1)	
EC50 96h - Algae [1]	22000 mg/l Source: ECHA
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

CRC® Ice-Off™ Windshield Spray De-Icer, 340 g	
Persistence and degradability	No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0.83 Source: ISCS

Methanol (67-56-1)	
BCF - Fish [1]	< 10 l/kg
Partition coefficient n-octanol/water (Log Pow)	-0.77 Source: HSDB,CHemIDplus

Water (7732-18-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.38

12.4. Mobility in soil

Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.8860566 – -0.21467016

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations. Dispose of contents/container in accordance with local/regional/national regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Do not allow to enter sewers, surface or groundwater.

Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols, flammable	AEROSOLS	Aerosols flammable, containing substances in Division 6.1, Packing Group III
14.3. Transport hazard class(es)		
2.1 (6.1)	2.1 (6.1)	2.1 (6.1)
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No supplementary information available		

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	:	2.1 - Class 2.1 - Flammable Gases
TDG Subsidiary Classes	:	6.1
UN-No. (TDG)	:	UN1950
TDG Special Provisions	:	80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment).
Explosive Limit and Limited Quantity Index	:	0.125 L
Excepted quantities (TDG)	:	E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	75 L
Emergency Response Guide (ERG) Number	:	126

IMDG

Class (IMDG)	:	2.1 - Flammable gases
Subsidiary hazard (IMDG)	:	6.1 - Toxic substances
Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

Class (IATA)	:	2.1 - Gases : Flammable
Subsidiary hazards (IATA)	:	6.1 - Toxic Substances

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provision (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10P

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® Ice-Off™ Windshield Spray De-Icer, 340 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Carbon dioxide	124-38-9	Listed on the Canadian DSL (Domestic Substances List)
Methanol	67-56-1	Listed on the Canadian DSL (Domestic Substances List)
Water	7732-18-5	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Carbon dioxide (124-38-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	89.9 %
Product Category	Not regulated.

SECTION 16: Other information

Issue date	:	03-18-2025
Revision date	:	07-28-2025
Supersedes	:	03-18-2025
Other information	:	CRC # 638/1002679.
Author		Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.