



CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-03-25 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Synthetic Brake & Caliper Grease, 340 g
Product code : 1006383
Part number : 75353

1.2. Recommended use and restrictions on use

Recommended use : Lubricating grease for brakes
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Not classified

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Precautionary statements (GHS CA) : Use only outdoors or in a well-ventilated area.
Observe good industrial hygiene practices.
Wash hands thoroughly after handling.
Store away from incompatible materials
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
polypropylene glycol monobutyl ether	α -Butyl- ω -hydroxypoly[oxy(methyl-1,2-ethanediyl)]	CAS-No.: 9003-13-8	80 – 100
Silica, amorphous, fumed, cryst.-free	Silicon dioxide	CAS-No.: 112945-52-5	5 – 10
Graphite	Graphite	CAS-No.: 7782-42-5	5 – 10
Molybdenum sulfide (MoS ₂)	Molybdenum sulfide	CAS-No.: 1317-33-5	1 – 5
ethanediol, ethylene glycol	1,2-Ethanediol ; Ethylene glycol	CAS-No.: 107-21-1	0.1 – 1

Full text of hazard classes and H-statements : see section 16

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth out with water.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Evacuate unnecessary personnel. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
Hygiene measures : Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store in a cool, dry place out of direct sunlight.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethanediol, ethylene glycol (107-21-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL C	100 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Ethylene glycol (vapour and mist)
Plafond (OEL C)	127 mg/m ³ 50 ppm
Notations and remarks	RP
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	10 mg/m ³ Total, aerosol only
OEL STEL	20 mg/m ³ Total, aerosol only
OEL C	100 mg/m ³ Total, aerosol only 50 ppm Vapour
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only) 50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only) 50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethanediol, ethylene glycol (107-21-1)	
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only) 50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Ethylene glycol, (as an aerosol)
OEL C	100 mg/m ³
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Ethylene glycol, (as an aerosol)
OEL C	100 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL C	100 mg/m ³ (H - Aerosol only)
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	25 ppm (V - Vapor fraction)
OEL STEL	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only) 50 ppm (V - Vapor fraction)
Notations and remarks	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Ethylene glycol, (as an aerosol)
OEL C	100 mg/m ³
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Graphite (7782-42-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Graphite (all forms except graphite fibres)

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Graphite (7782-42-5)	
OEL TWA	2 mg/m ³ respirable
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Graphite (all forms except fibers)
VEMP (OEL TWA _{EV})	2 mg/m ³ Rd
Notations and remarks	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Graphite - All forms except graphite fibres
OEL TWA	2 mg/m ³ Respirable
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Graphite (all forms excepte graphite fibers)
OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Graphite
OEL TWA	2 mg/m ³
Notations and remarks	Pneumoconiosis
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Graphite (all forms excepte graphite fibers)
OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Graphite (all forms excepte graphite fibers)
OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Graphite, natural-all forms except graphite fibres
OEL TWA	2 mg/m ³ (respirable fraction)

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Graphite (7782-42-5)	
OEL STEL	4 mg/m ³ (respirable fraction)
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Graphite, natural-all forms except graphite fibres
OEL TWA	2 mg/m ³ (respirable fraction)
OEL STEL	4 mg/m ³ (respirable fraction)
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Graphite (all forms except graphite fibers)
OEL TWAEV	2 mg/m ³ (R - Respirable fraction)
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Graphite (all forms excepte graphite fibers)
OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
Notations and remarks	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Graphite, natural-all forms except graphite fibres
OEL TWA	2 mg/m ³ (respirable fraction)
OEL STEL	4 mg/m ³ (respirable fraction)
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

Wear protective gloves such as: Nitrile

Eye protection:

Wear safety glasses with side shields (or goggles).

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: Black
Odor	: mild
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flammability (solid, gas)	: Non flammable.
Explosion limits	: Not applicable
Flash point	: 260 °C (500 °F) [Cleveland]
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: Not applicable
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: No data available
Density	: No data available
Relative density	: 1.01
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO ₂). Metal oxides. Sulfur oxides (SO _x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethanediol, ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg Source: ECHA
LD50 dermal	10600 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	> 2500 mg/l
Silica, amorphous, fumed, cryst.-free (112945-52-5)	
LD50 oral rat	> 3100 mg/kg Source: OECD Screening Information Data Set
Graphite (7782-42-5)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 2000 mg/l Source: ECHA
polypropylene glycol monobutyl ether (9003-13-8)	
LD50 oral rat	300 – 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	21000 mg/kg Source: National Library of Medicine/Hazardous Substances Data Bank
Molybdenum sulfide (MoS₂) (1317-33-5)	
LD50 dermal rabbit	> 2000 mg/kg Source: ChemIDplus
LC50 Inhalation - Rat	> 2820 mg/m ³
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Silica, amorphous, fumed, cryst.-free (112945-52-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Graphite (7782-42-5)	
NOAEL (oral,rat,90 days)	≥ 10000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Aspiration hazard	: Not classified
CRC® Synthetic Brake & Caliper Grease, 340 g	
Viscosity, kinematic	Not applicable
ethanediol, ethylene glycol (107-21-1)	
Viscosity, kinematic	14.459 mm ² /s
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ethanediol, ethylene glycol (107-21-1)	
LC50 - Fish [1]	72860 mg/l Source: ECHA
EC50 - Crustacea [1]	13900 – 57600 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	> 100 mg/l waterflea
EC50 - Other aquatic organisms [2]	6500 mg/l
ErC50 algae	> 1000 mg/l
EC50 96h - Algae [1]	6500 – 13000 mg/l Source: ECHA
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic crustacea	100 mg/l
Graphite (7782-42-5)	
LC50 - Fish [1]	100 mg/l Source: ECHA
EC50 - Crustacea [1]	100 mg/l Source: ECHA
ErC50 algae	100 mg/l Source: ECHA
EC50 72h - Algae [1]	19 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	7.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	47 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
polypropylene glycol monobutyl ether (9003-13-8)	
LC50 - Fish [1]	104 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Other aquatic organisms [1]	17 mg/l Source: ECOTOX

12.2. Persistence and degradability

CRC® Synthetic Brake & Caliper Grease, 340 g

Persistence and degradability : No data is available on the degradability of this product.

12.3. Bioaccumulative potential

ethanediol, ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.36

12.4. Mobility in soil

ethanediol, ethylene glycol (107-21-1)	
Mobility in soil	0.2 Source: HSDB

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

ethanediol, ethylene glycol (107-21-1)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0
--	---

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name		
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No supplementary information available		

14.6. Special precautions for user

TDG

Not applicable

:

IMDG

Not applicable

:

IATA

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 15: Regulatory information

15.1. National regulations

CRC® Synthetic Brake & Caliper Grease, 340 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
ethanediol, ethylene glycol	107-21-1	Listed on the Canadian DSL (Domestic Substances List)
Silica, amorphous, fumed, cryst.-free	112945-52-5	Listed on the Canadian DSL (Domestic Substances List)
Graphite	7782-42-5	Listed on the Canadian DSL (Domestic Substances List)
polypropylene glycol monobutyl ether	9003-13-8	Listed on the Canadian DSL (Domestic Substances List)
Molybdenum sulfide (MoS ₂)	1317-33-5	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

ethanediol, ethylene glycol (107-21-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Silica, amorphous, fumed, cryst.-free (112945-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Graphite (7782-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

polypropylene glycol monobutyl ether (9003-13-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Molybdenum sulfide (MoS₂) (1317-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

CRC® Synthetic Brake & Caliper Grease, 340 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

VOC content	0 %
Product Category	Not regulated.

SECTION 16: Other information

Issue date : 03-25-2025

Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.