



Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-07-15 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g
Product code : 1008257
Part number : 007088

1.2. Recommended use and restrictions on use

Recommended use : Protects from spatter build-up
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 3 Pressurized container; may burst if heated.

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : Pressurized container; may burst if heated

Precautionary statements (GHS CA) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

Wash hands thoroughly after handling.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No additional information available

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Fatty acids, C8-18 and C18-unsatd., compds. with diisopropanolamine	cocamide diisopropanolamine	CAS-No.: 68855-69-6	5 – 10
1,2,3-Propanetriol	Glycerol	CAS-No.: 56-81-5	1 – 3
Nitrogen	Nitrogen	CAS-No.: 7727-37-9	0.1 – 1

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a poison center/doctor/physician if you feel unwell.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : May cause mild irritation to the digestive tract.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Not flammable.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures	: Wear appropriate protective equipment and clothing during clean-up.

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Stop leak, if possible without risk.
Methods for cleaning up	: Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Do not use if spray button is missing or defective. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use. Wear personal protective equipment. For product usage instructions, see the product label.
Hygiene measures	: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Level 1 Aerosol. Store in a well-ventilated place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
--------------------	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Nitrogen (7727-37-9)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	Substance is a simple asphyxiant that may create an atmosphere deficient in oxygen; available oxygen in the range of 19.5 percent to 23 percent by volume must be present.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	Simple asphyxiant
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	Simple asphyxiant
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Ontario) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	Simple asphyxiant
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Nitrogen
Notations and remarks	TLV® Basis: Asphyxia

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Nitrogen (7727-37-9)	
Regulatory reference	ACGIH 2025
1,2,3-Propanetriol (56-81-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Glycerin mist
OEL TWA	10 mg/m ³
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Glycerin (mist)
VEMP (OEL TWAEV)	10 mg/m ³
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Glycerin - mist
OEL TWA	10 mg/m ³ Total 3 mg/m ³ Respirable
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Glycerin mist
Notations and remarks	URT irr
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Glycerin mist
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Glycerin mist
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Glycerin mist
OEL TWAEV	10 mg/m ³

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

1,2,3-Propanetriol (56-81-5)	
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Glycerin mist
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Nitrile. Neoprene.

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Red
Odor : mild
Melting point : 20 °C (68 °F) estimated
Freezing point : 20 °C (68 °F) estimated
Boiling point : 290 °C (554 °F) estimated
Flammability (solid, gas) : Not applicable
Explosion limits : No data available
Flash point : > 300 °C (>572 °F) estimated
Auto-ignition temperature : 392.8 °C (739 °F) estimated
Decomposition temperature : No data available

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

pH	: No data available
Viscosity, kinematic	: No data available
Solubility	: Water: Soluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: No data available
Density	: No data available
Relative density	: 1
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Acids. Alkalies. Oxidizing agent.
Hazardous decomposition products	: Carbon oxides (CO, CO ₂). Hydrocarbon fumes and smoke.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,2,3-Propanetriol (56-81-5)	
LD50 oral rat	27000 mg/kg Source: ECHA
LD50 dermal	> 18700 mg/kg body weight
LC50 Inhalation - Rat	5.85 mg/l air Animal: rat
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapors)	> 2.75 mg/l Source: ECHA

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

1,2,3-Propanetriol (56-81-5)	
LC50 - Fish [1]	54000 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea

12.2. Persistence and degradability

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Persistence and degradability : No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Nitrogen (7727-37-9)	
Partition coefficient n-octanol/water (Log Pow)	0.67 Source: National Library of Medicine/Hazardous Substances Data Bank
1,2,3-Propanetriol (56-81-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.75 Source: ECHA

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Contents under pressure.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information




In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, non-flammable (Limited quantity)

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

TDG	IMDG	IATA
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No		

14.6. Special precautions for user

TDG

TDG Primary Hazard Classes	: 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

IMDG

Class (IMDG)	: 2.2 - Non-flammable, non-toxic gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.2 - Gases : Non-flammable, Non-toxic
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A98, A145, A167, A802
ERG code (IATA)	: 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements, Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Name	CAS-No.	Regulatory reference
Nitrogen	7727-37-9	Listed on the Canadian DSL (Domestic Substances List)
1,2,3-Propanetriol	56-81-5	Listed on the Canadian DSL (Domestic Substances List)
Fatty acids, C8-18 and C18-unsatd., compds. with diisopropanolamine	68855-69-6	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Nitrogen (7727-37-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

1,2,3-Propanetriol (56-81-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Fatty acids, C8-18 and C18-unsatd., compds. with diisopropanolamine (68855-69-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	0.01 %
Product Category	Not regulated.

Weld-Aid® Weld-Kleen® 350 AP Anti-Spatter, 389 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 16: Other information

Issue date : 07-15-2025

Author Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.