



CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 3/28/2024 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® Pro-Strength Degreaser, 425 g
Product code : 1755538
Part number : 75481

1.2. Recommended use and restrictions on use

Recommended use : General purpose degreaser
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification


2.1. Classification of the substance or mixture

Classification (GHS CA)

Gases under pressure Liquefied gas : Contains gas under pressure; may explode if heated
Serious eye damage/eye irritation Category 2A : Causes serious eye irritation
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) : 

Signal word (GHS CA) : Warning

Hazard statements (GHS CA) : Contains gas under pressure; may explode if heated
Causes serious eye irritation

Precautionary statements (GHS CA) : Wash hands thoroughly after handling.
Wear eye protection, face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
Protect from sunlight. Store in a well-ventilated place.
Dispose of contents/container in accordance with local/regional/national regulations.

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2.3. Other hazards

Other hazards which do not result in classification : When exposed to extreme heat or hot surfaces, vapors may decompose to toxic gases such as hydrogen chloride and possibly phosgene.

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Water	Water	CAS-No.: 7732-18-5	60 - 80*
2-butoxyethanol; ethylene glycol monobutyl ether	2-Butoxyethanol ; Ethylene glycol monobutyl ether	CAS-No.: 111-76-2	1 - 5*
Butane	Butane	CAS-No.: 106-97-8	1 - 5*
Alcohols, C9-11, ethoxylated	Ethoxylated alcohols (C=9-11)	CAS-No.: 68439-46-3	1 - 5*
Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides	Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides	CAS-No.: 61791-10-4	1 - 5*
propane	Propane	CAS-No.: 74-98-6	0.5 - 1.5*
sodium carbonate	Sodium Carbonate	CAS-No.: 497-19-8	0.1 - 1*

*Contains fixed concentration

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
First-aid measures general : If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal use.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : When exposed to extreme heat or hot surfaces, vapors may decompose to toxic gases such as hydrogen chloride and possibly phosgene.

Explosion hazard : Pressurized container: may burst if heated.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Halogenated compounds. Hydrogen chloride. Nitrogen oxides. Phosgene. Sulphur oxides.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Pressurized container: Do not pierce or burn, even after use. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Level 1 Aerosol. Contents under pressure. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place.
Packaging materials	: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Ethylene glycol monobutyl ether)
OEL TWA	97 mg/m ³ 20 ppm
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl cellosolve®)
VEMP (OEL TWAEV)	20 ppm
Notations and remarks	C3
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
OEL TWA	20 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl Cellosolve or EGBE)
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl Cellosolve or EGBE)
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
OEL TWAEV	20 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
OEL TWA	20 ppm
Notations and remarks	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl Cellosolve or EGBE)
OEL TWA	20 ppm
OEL STEL	30 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
propane (74-98-6)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Propane

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

propane (74-98-6)	
VEMP (OEL TWAEV)	1800 mg/m ³ 1000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	Simple asphyxiant; EX (Substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Propane
Notations and remarks	See Appendix F: Minimal Oxygen Content
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Propane

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

propane (74-98-6)	
Notations and remarks	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Propane
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Butane (106-97-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Butane
OEL TWA	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Butane
VEMP (OEL TWAEV)	1900 mg/m ³ 800 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Butane, all isomers: n-butane
OEL STEL	1000 ppm
Notations and remarks	EX (Substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Butane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Butane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Butane
OEL STEL	1000 ppm (EX - Explosion hazard)

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Butane (106-97-8)	
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Butane, All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Butane, All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Butane, All isomers
OEL TWAEV	1000 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Butane
OEL STEL	1000 ppm (EX - Explosion hazard)
Notations and remarks	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Butane. All isomers
OEL TWA	1000 ppm
OEL STEL	1250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Neoprene or nitrile rubber gloves

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Eye protection:

Safety glasses with side shields

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Light yellow
Odor	: Mild odor
Melting point	: -74.8 °C estimated
Freezing point	: -74.8 °C estimated
Boiling point	: 100 °C estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: Lower explosion limit: 2.6 vol % estimated Upper explosion limit: 12.6 vol % estimated
Flash point	: None.
Auto-ignition temperature	: 150 °C estimated
Decomposition temperature	: No data available
pH	: 9.9
Viscosity, kinematic	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: 271 hPa estimated
Density	: 8.66 lb/gal Concentrate
Relative density	: 1.04 Concentrate
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Other information

VOC content	: 9.7 %
-------------	---------

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Carbon oxides (CO, CO ₂). Nitrogen oxides. Sulphur oxides. Halogenated compounds. Hydrogen chloride. Phosgene.

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
LD50 oral	1746 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal	435 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	2200 mg/l

sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg Source: OECD Screening Information Data Set
LD50 oral	4090 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg Source: OECD Screening Information Data Set
LD50 dermal	> 2000 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	1.2 mg/l Source: SIDS

Alcohols, C9-11, ethoxylated (68439-46-3)	
LD50 oral rat	1378 mg/kg Source: Corporate Solution From Thomson Micromedex
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	2000 mg/kg Source: Corporate Solution From Thomson Micromedex
LC50 Inhalation - Rat	> 1.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Water (7732-18-5)	
LD50 oral rat	90000 mg/kg
LD50 oral	> 90000 mg/kg body weight
LD50 dermal	> 90000 mg/kg body weight

propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	800000 ppm Source: ECHA

Butane (106-97-8)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm Source: ECHA

Skin corrosion/irritation : Not classified
pH: 9.9

sodium carbonate (497-19-8)	
pH	11.5 Source: Corporate Solution From Thomson Micromedex

Alcohols, C9-11, ethoxylated (68439-46-3)	
pH	6 – 7.5

Water (7732-18-5)	
pH	7

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Serious eye damage/irritation : Causes serious eye irritation.
pH: 9.9

sodium carbonate (497-19-8)	
pH	11.5 Source: Corporate Solution From Thomson Micromedex
Alcohols, C9-11, ethoxylated (68439-46-3)	
pH	6 – 7.5
Water (7732-18-5)	
pH	7

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified.

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
NOAEL (dermal,rat,rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Alcohols, C9-11, ethoxylated (68439-46-3)	
NOAEL (oral,rat,90 days)	≥ 500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified
Symptoms/effects after inhalation : None under normal use.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	1550 mg/l waterflea
EC50 - Other aquatic organisms [2]	911 mg/l
EC50 72h - Algae [1]	911 mg/l Source: ECHA
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

sodium carbonate (497-19-8)	
LC50 - Fish [1]	300 mg/l Source: International Uniform Chemical Information Database
EC50 - Crustacea [1]	200 – 227 mg/l Source: OECD Screening Information Data Set
EC50 - Crustacea [2]	200 – 227 mg/l Test organisms (species): Ceriodaphnia sp.
EC50 - Other aquatic organisms [1]	265 mg/l waterflea
EC50 96h - Algae [1]	242 mg/l Source: ECOTOX
Alcohols, C9-11, ethoxylated (68439-46-3)	
LC50 - Fish [1]	8.5 mg/l Source: ECOTOX
EC50 - Crustacea [1]	2.686 mg/l Source: ECOTOX
EC50 96h - Algae [1]	1.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
propane (74-98-6)	
LC50 - Fish [1]	> 100 mg/l Source: IUCLID
Butane (106-97-8)	
LC50 - Fish [1]	27.98 mg/l Source: QSAR
EC50 96h - Algae [1]	16.47 mg/l Source: QSAR
12.2. Persistence and degradability	
CRC® Pro-Strength Degreaser, 425 g	
Persistence and degradability	No data is available on the degradability of this product.
12.3. Bioaccumulative potential	
2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 Source: ECHA
sodium carbonate (497-19-8)	
Partition coefficient n-octanol/water (Log Pow)	-6.19 Source: Quantitative Structure Activity Relation
Water (7732-18-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.38
propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	2.36
Butane (106-97-8)	
Partition coefficient n-octanol/water (Log Pow)	2.89 Source: ICSC
12.4. Mobility in soil	
Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides (61791-10-4)	
Mobility in soil	0.2083 Source: EPISUITE

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Do not allow to enter sewers, surface or groundwater. Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, non-flammable (Limited quantity)
14.3. Transport hazard class(es)		
2.2	2.2	2.2
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

TDG
UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A98, A145, A167, A802
ERG code (IATA)	: 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Other information Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268. Product Category: General-purpose degreaser, excluding any product that is designed for use solely in solvent cleaning tanks or related equipment.

2-butoxyethanol; ethylene glycol monobutyl ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Alcohols, C9-11, ethoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides (61791-10-4)

Listed on the Canadian DSL (Domestic Substances List)

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

CRC® Pro-Strength Degreaser, 425 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: Other information

Issue date : 03/28/2024

Other information : CRC # 692A/1002737.

Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.